

# Product data sheet

## Gjøco Vinduskitt



Gjøco Window Putty is a putty based on linseed oil and vegetable oils, ready for use. It is used for glazing windows and repairing window frames. It can also be used for filling nail holes, among other purposes. Gjøco Window Putty must be painted over to ensure good durability.

Revised 27.11.2024

Symbols



### Technical Data

Type:	Linseed oil-based putty
Color:	White and natural
Density:	Approx. 2.1 kg/l
Application Method	Steel spatula, putty knife, caulking gun
Thinner / Cleaning Agent	White spirit
Touch-dry:	Approx. 0.5 hours
Layer Thickness	Max. 3 mm
Recommended Application Temperature::	Min. +5°C, max. +40°C
Shelf Life:	2 years in unopened packaging. May remain usable longer as long as the putty has not dried out.

### Preparation

The surface must be clean, dry, grease-free, and free of loose particles. Bare wood and the glazing rebate should be primed with paint or Gjøco Oil Primer before applying the putty.

### Usage Instructions

Apply using a steel spatula or putty knife. Avoid exposing the putty to heavy rain or strong sunlight until it has cured sufficiently. Paint over the putty after 2–4 weeks. When painting, extend the paint 1–2 mm onto the glass.

### Storage

Seal the lid tightly when storing the putty to prevent spills and drying out. Store and transport upright, frost-free, and away from high temperatures.

### Waste Disposal

The product must not be poured into drains or released into the environment. It should be delivered to a recycling center. Empty, clean, and dry plastic packaging can be disposed of as plastic waste.

### Additional Information

Stir well before use. Uncured putty can be removed with paper towels or Gjøco White Spirit. Packaging Sizes: 375 ml tin or 300 ml cartridge.

---

**Safety**

Refer to the dedicated safety data sheet. Read the information on the packaging.

---

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and since the conditions under which they are used are often beyond our control, we can only guarantee the quality of the product itself. The products are supplied in accordance with our general terms of sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product modifications and to change the stated data without prior notice. This data sheet supersedes previous versions.

---

**Contact Information**

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukt  
Phone number: +47 712 91 700  
Email: [office@gjoco.no](mailto:office@gjoco.no)

