

Product datasheet

Gjøco Båtlakk



Gjøco Boat Paint is a glossy and durable paint with high water resistance. Provides a hard and flexible surface that is easy to keep clean. Contains light filters that protect the surface. Can be used inside and outside above the waterline.

Revised 13.03.2025

Symbols




Technical data

Type:	Urethane alkyd-based varnish
Color:	Transparent
Gloss:	Gloss
Specific gravity:	0.88 kg/l
Solid content:	Approx. 51 volum%
Application method:	Brush, roller or high-pressure spray. Spraying is recommended for professionals only.
Thinner / cleaning agent:	White Spirit
Recommended spreading rate:	Approx. 12-15 m ² /liter, depending on surface.
Recommended film thickness, wet:	100 micrometers
Recommended film thickness, dry:	40 micrometers
Guiding data for airless spray:	
Nozzle:	0,021"; 0,53 mm
Spray angel:	65°-80°
Pressure at nozzle:	150 kg/cm ²
Drying time (23 °C, 50 % R.H.):	
Dust dry:	5 hours
Interval between coats:	12 hours. Full adhesion is achieved after 4 weeks of curing. Deviates due to changes in temperature, humidity, ventilation and film thickness.

Pretreatment

The substrate must be clean and dry, and free of grease, wax and soap residue. Grease and contamination must be removed with Gjøco Husvask or Gjøco Kraftvask. Follow the instructions on the packaging. Let dry before further

	treatment. Sand the surface until it is matt and smooth. Remove sanding dust thoroughly.
Directions for use	On bare and sanded wood, thin the varnish with 20% White spirit for the first coat. Light sanding with P230 – P320 is recommended between coats to ensure good adhesion. Remove sanding dust thoroughly. Apply the varnish in the lengthwise direction of the boards. Can be used on parquet, wooden floors, panels, cork, furniture, doors and windows.
Storage	Close the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
Disposal of waste	Liquid paint and washing water must not be emptied into sewers or into nature, but must be delivered to an environmental station. 
Other information	Stir well before use. Different batch numbers are mixed before use to avoid differences in gloss. Thick coats and low temperatures extend drying time. Do not expose the varnish to wear until it has fully cured (3-4 days). Package sizes: 0.75 liters.
Safety	See separate safety data sheet. Read the information on the packaging. EU limit value for this product (kat. A/e): 400 g/l (2010). This product contains: <400 g/l VOC.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information

Gjøco AS
 Ørvegen 1160, 6639 Torvikbukt
 Telephone: +47 712 91 700
 E-mail: office@gjoco.no

