



F DV – Management, Operation, and Maintenance

Gjøco Dekksolje



Gjøco Dekksolje is an impregnating oil based on pure wood tar, turpentine, alkyds, and a film-preserving agent against mildew, intended for wooden boats and docks.

Revised

13.03.2025

Usage Instructions

Surface Preparation:

The surface must be clean and dry, with a minimum temperature of +10 °C.

Application Method:

Brush.

Thinner:

White spirit or turpentine.

Storage:

Store and transport upright, in a dry and frost-free place, out of reach of children.

Transport:

Not classified as dangerous goods according to applicable regulations.

Indoor Environment/Emissions:

The product is intended for outdoor use.

Technical and Safety Data

A technical data sheet and safety data sheet (SDS/HMS) have been prepared for the product. See www.gjoco.no. VOC: EU limit for the product (cat. A/f): 700 g/l (2010). The product contains <650 g/l VOC.

Maintenance

Cleaning:

For annual cleaning, Gjøco House Wash is recommended. If surfaces are contaminated with mildew, they can additionally be treated with Gjøco Mold and Green Remover. For cleaning before repainting, Gjøco Power Wash is recommended. Follow the instructions on the product. Newly painted wood should not be washed until after 3-4 weeks.

Interval:

The paint film naturally degrades due to weather exposure, varying with local conditions. Repainting must be done as needed when the film becomes dull and worn.

Waste Management

Liquid paint and wash water must not be poured into sewage systems or nature but should be delivered to a recycling station.

**Repairs/Damages**

Repairs and damages should be addressed with the same type of product. Documentation is required if other products are used to ensure they are of the same type. Repairs must be carried out to match previous treatments. For repainting or color changes, the same product as previously used is recommended. Contact the retailer or painting company.

Treated Surface/Type of Substrate:

.....

Painted in color:**Color name:**

.....

NCS:

.....

Batch number:

.....

Painting performed by:

.....

Date:

.....

Signature:

.....

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as the conditions under which they are used are often beyond our control, we can only guarantee the product's quality. The products are delivered in accordance with our general terms of sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and to modify the specified data without prior notice. This data sheet replaces previous versions and automatically becomes invalid five years after the publication date.

Contact Information**Gjøco AS**

Ørvegen 1160, 6639 Torvikbukt

Phone: +47 712 91 700

Email: office@gjoco.no

