



F DV – Management, Operation, and Maintenance

Gjøco Emaljelakk



Gjøco Emaljelakk is a glossy and durable topcoat designed for primed substrates of metal, wood, and hard plastic. It is used for agricultural tools, iron constructions, machinery, gate posts, fences, wrought iron gates, bicycles, garden furniture, furniture, interior fixtures, lamps, pots, candlesticks, flagpoles, etc. It is also suitable for use on wooden details on boats above the waterline.

Revised 06.03.2025

Usage Instructions	Surface Preparation:	The surface must be clean and dry.
	Application Method:	Brush, roller, or spray.
	Thinner:	White spirit.
	Storage:	Store and transport upright, in a dry and frost-free place, out of reach of children.
	Transport:	Not classified as dangerous goods according to applicable regulations.
	Indoor Environment/Emissions:	The product is intended for outdoor use.
Technical and Safety Data	A technical data sheet and safety data sheet (SDS/HMS) have been prepared for the product. See www.gjoco.no . VOC: EU limit for the product (cat. A/f): 500 g/l (2010). The product contains <450 g/l VOC.	
Maintenance	Cleaning:	Painted surfaces should not be washed until after 3-4 weeks. For annual cleaning, Gjøco Husvask is recommended.
	Interval:	The paint film naturally degrades due to weather exposure, varying with local conditions. Repainting must be done as needed when the film becomes dull and worn. Exposed surfaces degrade faster and require more frequent repainting.

Waste Management

Liquid paint and wash water must not be poured into sewage systems or nature but should be delivered to a recycling station.



Repairs/Damages

Repairs and damages should be addressed with the same type of product. Documentation is required if other products are used to ensure they are of the same type. Repairs must be carried out to match previous treatments. For repainting or color changes, the same product as previously used is recommended. Contact the retailer or painting company.

Treated Surface/Type of Substrate:

.....

Painted in color:

Color name:

.....

NCS:

.....

Batch number:

.....

Painting performed by:

Date:

.....

Signature:

.....

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as the conditions under which they are used are often beyond our control, we can only guarantee the product's quality. The products are delivered in accordance with our general terms of sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and to modify the specified data without prior notice. This data sheet replaces previous versions and automatically becomes invalid five years after the publication date.

Contact Information

Gjøco AS

Ørvegen 1160, 6639 Torvikbukt, Norway

Phone: +47 712 91 700

Email: office@gjoco.no

