



## FDV – Management, operation, and maintenance

# Gjøco Herregård Exclusive Oljedekkbeis



Gjøco Herregård Exclusive Oljedekkbeis is a durable, weather-resistant, and thixotropic oil-based stain made from high-quality alkyds. It is used on exterior woodwork and provides a subdued wood texture. It is especially well-suited for weather-exposed areas and offers good protection against fading and wear. Herregård Exclusive Oljedekkbeis contains an extra film-preserving anti-mold agent and UV-protective substances. It is used on new and primed wood, as well as previously stained or painted exterior planed or unplanned wood.

Revised 11.03.2025

<b>Application Instructions</b>	<b>Substrate:</b>	The surface must be clean, dry, and have a minimum temperature of 0°C.
	<b>Application Methods:</b>	Brush, roller, or spray. Spraying should be performed by professionals.
	<b>Thinner:</b>	White Spirit, thinning is usually not necessary.
	<b>Storage:</b>	Store and transport upright, dry, and frost-free, out of reach of children.
	<b>Transport:</b>	Not classified as dangerous goods under applicable regulations.
	<b>Indoor Environment/Emission:</b>	The product is intended for outdoor use.

**Technical and Safety Data** A technical data sheet and safety data sheet (SDS / MSDS) have been prepared for the product. See [www.gjoco.no](http://www.gjoco.no). VOC: EU limit for the product (cat. A/e): 400 g/l (2010). The product contains <400 g/l VOC.

<b>Maintenance</b>	<b>Cleaning:</b>	For annual cleaning, Gjøco Husvask is recommended. If surfaces are contaminated with mold, they can also be treated with Gjøco Sopp- og grønskefjerner. For cleaning before repainting, Gjøco Kraftvask is recommended. Follow the instructions on the product. Newly painted wood should not be washed before 3-4 weeks.
	<b>Interval:</b>	The paint film naturally breaks down due to weather exposure and will vary depending on local conditions. Repainting should therefore be done as needed, when the film becomes matte and worn. The weather-facing wall(s) are more exposed to the elements and typically require more frequent repainting than the rest of the building.

---

**Waste Disposal**

Liquid paint should not be disposed of in sewage drains or in nature, but should be delivered to an approved facility for hazardous waste. Empty and dry packaging should be delivered to an approved facility. See the regulations for hazardous waste for further details.



---

**Repairs/Damage**

Repairs and damages should be addressed using the same product type. Documentation must prove the same product type was previously used if other products are applied. Repairs should match the existing treatment. For repainting or color changes, it is recommended to use the same product as before. Contact a retailer or painting company for assistance.

---

**Surface/Material Information**

**Painted in color:**

**Color name:**

**NCS:**

**Batch number:**

**Work performed by:**

**Date:**

**Signature:**

---

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

---

**Contact Information**

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukt  
Phone: +47 712 91 700  
Email: office@gjoco.no

