



## FDV – Management, operation, and maintenance

### Herregård Maximal



Herregård Maximal is an opaque wood protection for outdoor use. It contains film-preserving agents that prevent the growth of mold. Herregård Maximal is a durable and gloss-stable high-quality paint that provides wood with excellent protection against weathering and the degradation caused by sunlight. Herregård Maximal can be used on exterior new, old, stained, painted, or pressure-treated wood. It can also be used as a topcoat on primed metal and plastic materials, such as gutters, flashings, and similar parts on buildings.

Revised

15.08.2025

#### Application Instructions

##### Substrate:

The surface must be clean, dry, and have a minimum temperature of +5°C.

##### Application Methods:

Roller, or spray. Spraying should be performed by professionals.

##### Thinner:

Water, thinning is usually not necessary.

##### Storage:

Store and transport upright, dry, and frost-free, out of reach of children.

##### Transport:

Not classified as dangerous goods under applicable regulations.

##### Indoor Environment/Emission:

The product is intended for outdoor use.

#### Technical and Safety Data

A technical data sheet and safety data sheet (SDS / MSDS) have been prepared for the product. See [www.gjoco.no](http://www.gjoco.no). VOC: EU limit for the product (cat. A/e): 130 g/l (2010). The product contains <30 g/l VOC.

#### Maintenance

##### Cleaning:

For annual cleaning, Gjøco Husvask is recommended. If other cleaning agents are used, the pH value should not exceed pH 9. For cleaning before repainting, Gjøco Kraftvask is recommended. Follow the instructions on the product. Newly painted wood should not be washed before 3-4 weeks.

##### Interval:

The paint film naturally breaks down due to weather exposure and will vary depending on local conditions. Repainting should therefore be done as needed, when the film becomes matte and worn. Weather-facing wall(s) are more exposed to the elements and typically require more frequent repainting than the rest of the building.

**Waste Disposal**

Liquid paint should not be disposed of in sewage drains or in nature, but should be delivered to an approved facility for hazardous waste. Empty, clean, and dry plastic packaging without handles can be disposed of as plastic waste.

**Repairs/Damage**

Repairs and damages should be addressed using the same product type. Documentation must prove the same product type was previously used if other products are applied. Repairs should match the existing treatment. For repainting or color changes, it is recommended to use the same product as before. Contact a retailer or painting company for assistance.

**Surface/Material Information****Painted in color:****Color name:****NCS:****Batch number:****Work performed by:****Date:****Signature:**

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

**Contact Information****Gjøco AS**

Ørvegen 1160, 6639 Torvikbukt

Phone: +47 712 91 700

Email: office@gjoco.no

