

FDV – Management, Operation and Maintenance

Gjøco Fashion 05



Gjøco Fashion 05 is a water-thinnable, low-odor oil-based paint for indoor use. It has excellent application properties and provides a durable and elegant finish. Suitable for intermediate and topcoats on paneling, MDF, doors, windows, frames, moldings, and interior fittings.

Revised

07.01.2025

Usage Instructions

Surface Preparation:

Ensure the surface is clean and dry, with a minimum temperature of +10°C

Application Method:

Brush, roller, or spray. Spraying should be performed by professionals.

Thinner:

Water; thinning is usually not necessary.

Storage:

Store and transport upright, dry, frost-free, and out of reach of children.

Transport:

Not classified as hazardous goods under applicable regulations.

Indoor Environment/Emissions

The product emits low emissions.

Technical and Safety Data

A technical data sheet and safety data sheet (SDS) are available at www.gjoco.no. VOC Content: EU limit for the product (cat. A/a): 130 g/l (2010). This product contains <75 g/l VOC.

Maintenance

Cleaning:

Use an alkaline cleaning agent like Gjøco Interiørvask or Husvask for cleaning before repainting. Follow the product instructions. Newly painted surfaces should not be washed for 4 weeks. Use microfiber cloths with clean water or mild soapy water. The water temperature should not exceed +40°C, and the pH should not exceed 9. Avoid abrasive cleaning agents to prevent surface damage. Perform cleaning in a way that avoids streaks, based on discretion. The paint film wears faster with frequent cleaning.

Intervals:

Maintenance intervals depend on the degree of mechanical impact and wear.

Waste Management

The product is classified as hazardous waste and must be delivered to an approved hazardous waste facility. Do not pour the product into the environment, sewage, or water. Empty and dry packaging must be delivered to an approved facility. Refer to additional regulations for hazardous waste.



Repairs/Damage

Repairs should be done with the same type of product. Documentation is required if another product is used. Ensure repairs blend seamlessly with previous treatments. For repainting or color changes, use the same product as previously applied. Contact your dealer or painting company for guidance.

Environmental Labeling

The product is approved by Nordic Swan Ecolabel (Svanen) and meets its requirements.



The product has been tested according to BREEAM-NOR requirements and satisfies BREEAM-NOR HEA 02.
Gjøco Alle Rom contains no substances on the A20 list.

Treated Surface/Type of Substrate:

.....

Painted in Color:

Color Name:

.....

NCS:

.....

Batch Number:

.....

Painting Performed By:

.....

Date:

.....

Signature:

.....

The information in this data sheet is based on laboratory tests and practical experience. As our products are semi-finished goods, and usage conditions often fall outside our control, we only guarantee the product's quality. Products are delivered under our general terms of sale, delivery, and service unless otherwise agreed in writing. Minor product changes and data updates may occur without notice. This data sheet replaces previous editions and is automatically invalidated five years after its issue date.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Phone: +47 712 91 700
Email: office@gjoco.no

