

FDV – Management, Operation, and Maintenance Gjøco Proff Lettsparkel Våtrom



Proff Lettsparkel Våtrom is a medium-grained lightweight hand filler for indoor use in wet rooms. It is used for leveling and joint filling on building boards such as chipboard, fiberboard, and gypsum boards. When joint filling gypsum boards, paper tape must be used.

| Revised: | 11.06.2025 | |
|--|---|---|
| Instructions for Use | Substrate: | The surface must be clean and dry. |
| | Туре: | Latex polymer with aluminum silicate and white dolomite as fillers. |
| | Application method: | Steel trowel |
| | Cleaning agent: | Water. |
| | Thinner: | Normally should not be thinned. |
| | Storage: | Store in a dry and frost-free place, out of reach of children. |
| | Transport: | Not classified as hazardous goods according to current regulations. |
| Technical Data and Safety Information | A technical data sheet and a safety data sheet (HMS / SDS) have been prepared for the product. See www.gjoco.no. | |
| Maintenance | Cleaning: | Not applicable. The product is not used on its own. |
| | Interval: | Not applicable. The product is not used on its own. |
| Waste Disposal | The product must be delivered to an approved facility for such waste. The product must not be poured into the environment, sewage, or water. Empty and dry packaging should be delivered to an approved facility. | |
| Repairs / Damage | Repairs and damage should be repaired using the same type of product. If other products are used, it must be documented that they are of the same type as previously used. When repairing damage, the work should be carried out so that it does not differ from previous treatments. When repaining or changing color, it is recommended to use the same product as before. Contact your dealer or paint | |

company for advice.

| ajøco - Filler | | |
|---|---|------------------------------------|
| | | |
| | | |
| Freated Surface / Type of Substrate: | | |
| Batch Number: | | |
| Painting Work Performed By | : | |
| Date: | | |
| Signature: | | |
| conditions under which the products are supplied in accordance with our genera | sed on laboratory tests and practical experience. Our products are considered semi-finished gov e used are often beyond our control, we can only guarantee the quality of the product itself. The I terms and conditions for sales, delivery, and service, unless otherwise agreed in writing. We re then the specified data without prior notice. This data sheet replaces previous versions and is a | products are serve the right to |
| Contact Information | Gjøco AS | |
| | Ørvegen 1160, 6639 Torvikbukt, Norway Phone: +47 712 91 700 | GJØ(O |

Email: office@gjoco.no