

## Product Data Sheet

## Gjøco Proff Lettsparkel Våtrom



Proff Lettsparkel Våtrom is a medium-grade lightweight filler designed for indoor use in wet rooms. It is used for leveling and joint filling on construction boards such as chipboard, MDF, and gypsum boards. When joint filling on gypsum boards, paper tape should be used.

Revised 05.12.2024

Symbols



### Technical Data

Type:	Latex copolymer with dolomite and aluminum silicate as fillers
Color:	Light gray/green
Density:	Approx. 1 kg/l
Solids Content	Approx. 58%
pH:	Approx. 9
Grain Size:	Max 0,2 mm
Application Method:	Steel trowel
Thinner/Cleaning Agent:	Water. Normally should not be thinned.
Consumption:	Wide spreading: 1 liter/m <sup>2</sup> at 1 mm film thickness
Drying Time:	Depends on substrate, layer thickness, temperature, and humidity
Touch Dry:	Approx. 0,5 hours
Repainting Interval, Minimum:	Approx. 24 hours
Layer Thickness:	Max. 3 mm
Minimum Application Temperature:	+5°C
Shelf Life:	1 year in unopened packaging

### Surface Preparation

The substrate must be clean, dry, grease-free, and free of loose particles. Glossy surfaces should be cleaned with Gjøco Husvask or Gjøco Interiørvask.

### Application

Apply with a steel trowel. Sanding should be done with fine sandpaper (100-120 grit).

### Storage

Seal the lid tightly when storing the filler to prevent spillage and drying out. Transport and store upright, in dry and frost-free conditions.

---

**Waste Disposal**

Do not dispose of filler or washing water in sewers or nature. Deliver to an approved hazardous waste facility. Empty, clean, and dry plastic packaging can be disposed of as plastic waste.



---

**Additional Information**

Store in a dry, frost-free location, away from direct sunlight. Unopened packaging can be stored for 12 months. It may remain usable after 12 months; check consistency and smell. Packaging size: 400L, 3L and 10L.

---

**Safety**

Refer to the dedicated safety data sheet. Read the information on the packaging. Use eye protection when sanding large areas.

---

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and since conditions of use are often beyond our control, we can only guarantee the product's quality. Products are supplied according to our general terms of sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and update the stated data without prior notice. This data sheet supersedes earlier versions.

---

**Contact Information**

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukt  
Phone: +47 712 91 700  
Email: [office@gjoco.no](mailto:office@gjoco.no)

