



FDV – Management, operation, and maintenance

Gjøco Taksteinolje



Gjøco Taksteinolje is a weather-resistant oil for outdoor use on roofs. It has high water-repellent properties and good weather resistance. It contains a film-preserving agent to prevent the growth of black mold, moss, and algae. It is suitable for most types of roof tiles such as concrete, clay, cement tiles, and asbestos cement. It is not suitable for certain types of super/flat asbestos cement that are very smooth.

Revised

15.01.2025

Application Instructions	Substrate:	The surface must be clean and dry, with a minimum temperature of 0 °C.
	Application Methods:	Wide brush designed for oil. Spraying should be done by professionals.
	Thinner:	White Spirit.
	Storage:	Store and transport upright, dry, and frost-free, out of reach of children.
	Transport:	Not classified as dangerous goods under applicable regulations.
	Indoor Environment/Emission:	The product is intended for outdoor use.
Technical and Safety Data	A technical data sheet and safety data sheet (SDS/HMS) have been prepared for the product. See www.gjoco.no . VOC: EU limit for the product (category A/e): 400 g/l (2010). The product contains <400 g/l VOC.	
Maintenance	Cleaning:	For annual cleaning, Gjøco Husvask is recommended. If surfaces are contaminated with black mold, they can also be treated with Gjøco Sopp- og grønskefjerner. For cleaning before repainting, Gjøco Kraftvask is recommended. Follow the instructions on the product.
	Interval:	The paint film naturally breaks down due to weather exposure and will vary based on local conditions. Repainting must therefore be done as needed, when the film appears dull and worn. The weather wall(s) are more exposed to the weather and typically require more frequent repainting than the rest of the building.

Waste Disposal

Liquid paint should not be disposed of in sewer drains or in nature, but should be delivered to an approved hazardous waste facility. Empty and dry packaging should be delivered to an approved facility. For further information, refer to the regulations for hazardous waste.



Repairs/Damage

Repairs and damages should be addressed with the same type of product. Documentation must be provided to confirm it is the same type previously used if other products are employed. Repairs should be carried out to match previous treatments. For repainting or color changes, it is recommended to use the same product as before. Contact the dealer or paint company for advice.

Surface/Material Information

Painted in color:

Color name:

NCS:

Batch number:

Work performed by:

Date:

Signature:

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbuk
Phone: +47 712 91 700
Email: office@gjoco.no

