

Product datasheet

Gjøco Taksteinolje



Gjøco Taksteinolje is a weather-resistant oil for outdoor use on roofs. It has a high water-repellent effect and good weather resistance. Contains a film preservative against the growth of black fungus, green mold and algae. Used on most types of roof tiles such as concrete, brick, cement brick and eternit. Not suitable for certain types of super/flat eternit which are very slippery.

Revised 11.12.2024

Symbols




Technical data

Type:	Alkyd oil-based oil
Color:	Red and black
Flash point:	>62 °C
Specific gravity:	1.1 kg/l
Solid content:	Approx. 61 volum%
Application method:	Wide brush intended for oil. Spraying is recommended to be done by professionals.
Thinner / cleaning agent:	White Spirit
Recommended spreading rate:	Depending on the substrate.
First coat:	2-4 m ² /liter
Second coat:	5-8 m ² /liter
Guiding data for airless spray:	
Nozzle:	0,46 mm / 0,018"
Spray angel:	65°-80°
Pressure at nozzle:	MPa 15-18 / 150 kg/cm ²
Drying time (23 °C, 50 % R.H.):	Depends on temperature, humidity, wind and film thickness. Low temperature extends drying time.
Dust dry:	8-12 hours
Interval between coats, minimum:	12-24 hours
Minimum application temperature:	+5 °C

Pretreatment

The substrate must be clean, firm and dry. All fouling such as fungus, moss, greens and algae must be removed. Any loose paint, stain or oil from previous treatment must be removed by scraping/brushing. Clean with Gjøco Husvask or

	Gjøco Kraftvask. Follow the instructions on the packaging. Remember to cover windows and wall surfaces, or rinse with clean water to avoid peeling.
Directions for use	On highly absorbent surfaces, the first coat can be thinned with 15-20% Gjøco White Spirit. Then apply one to two top coats undiluted. If only a refresh of gloss and color is desired, one coat may be sufficient. When using a paint sprayer, care must be taken to ensure that spray mist does not go astray.
Storage	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
Disposal of waste	Liquid paint should not be emptied into sewers or into the environment, but delivered to an approved hazardous waste collection point. Empty, clean and dry packaging should be delivered to an approved collection point. 
Other information	Any oil float should be stirred in well for a while before use. The contents of cans with different batch numbers should be mixed before use to avoid color differences. The substrate must be firm, clean and dry before applying the oil. Dew on a semi-dry surface can cause matt spots. Matt spots can also occur when drying at high humidity and low temperatures, such as in spring and autumn. Sun on a wet or semi-dry surface can cause leather drying and blistering. Do not use on frosted surfaces. Application temperature in air and substrate must be at least +5 °C. Take a test coat if unsure about the substrate. For more detailed information, see safety and technical data sheet.
Safety	See separate safety data sheet. Read the information on the packaging. EU limit value for this product (kat. A/e): 400 g/l (2010). This product contains: <400 g/l VOC.
<p>The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.</p>	
Contact information	Gjøco AS Ørvegen 1160, 6639 Torvikbukt Telephone: +47 712 91 700 E-mail: office@gjoco.no 