

# FDV – Management, Operation and Maintenance

## Gjøco Kalkmaling



Gjøco Kalkmaling is a mineral-based lime paint for interior use in dry rooms. It provides a lively, concrete-like surface. It is used on building panels, plaster, concrete, and plastered surfaces. In areas with a risk of wear, moisture, and water spillage, the application of Gjøco Sealer as a topcoat is recommended

Revised

07.01.2025

### Usage Instructions

<b>Substrate:</b>	Ensure the surface is clean and dry, with a minimum temperature of +10°C
<b>Application Method:</b>	Brush.
<b>Thinner:</b>	Water, thinning is generally not necessary.
<b>Storage:</b>	Store and transport upright, dry, frost-free, and out of reach of children.
<b>Transport:</b>	Not classified as hazardous goods under applicable regulations.
<b>Indoor Environment/Emissions</b>	The product emits low emissions.

### Technical and Safety Data

A technical data sheet and safety data sheet (SDS / HSE data sheet) have been prepared for the product. See [www.gjoco.no](http://www.gjoco.no). VOC: The EU limit value for the product (category A/i): 200 g/l (2010). The product contains <30 g/l VOC.

### Maintenance

<b>Cleaning:</b>	Avoid washing with water. Dust gently with a dry cloth. For durability and water resistance, it is recommended to apply a coat of Gjøco Sealer.
<b>Intervals:</b>	The paint film is affected by mechanical impact and wears according to the level of stress. Maintenance intervals will therefore vary based on need.

### Waste Management

The product is classified as hazardous waste and must be delivered to an approved hazardous waste disposal facility. The product must not be poured into the environment, sewage, or water. Empty, clean, and dry plastic packaging without handles can be disposed of as plastic waste. Refer to applicable regulations for hazardous waste.



**Repairs/Damage**

Repairs and damages should be addressed using the same type of product. If other products are used, it must be documented that they are of the same type previously applied. Repairs should be carried out in a way that does not deviate from previous treatments. For repainting or color changes, it is recommended to use the same product as previously applied. Contact your dealer or a painting company for assistance.

**Treated Surface/Type of Substrate:**

.....

**Painted in Color:**

**Color Name:**

.....

**NCS:**

.....

**Batch Number:**

.....

**Painting Performed By:**

.....

**Date:**

.....

**Signature:**

.....

The information in this data sheet is based on laboratory tests and practical experience. As our products are semi-finished goods, and usage conditions often fall outside our control, we only guarantee the product's quality. Products are delivered under our general terms of sale, delivery, and service unless otherwise agreed in writing. Minor product changes and data updates may occur without notice. This data sheet replaces previous editions and is automatically invalidated five years after its issue date.

**Contact Information**

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukt  
Phone: +47 712 91 700  
Email: office@gjoco.no

