

Product datasheet

Gjøco Sealer



Gjøco Sealer is a transparent acrylic-based matt treatment for sealing matt and/or pigmented surfaces to improve wear resistance, colour transfer and water resistance. Gjøco Sealer is suitable for use as a topcoat over Gjøco Lime Paint on surfaces that may be exposed to water spills and wear. Can also be used on other paints where there are problems with colour transfer and to increase water resistance. Not intended for use on floors.

Revised 03.12.2024

Symbols



Technical data


Type:	Akrylbasert dispersjon
Color:	Clear
Gloss:	03
Specific gravity:	1.01 kg/l
Solid content:	Ca. 26 volum%
Application method:	Brush or roller.
Thinner/ cleaning agent:	Water
Recommended spreading rate:	10-15 m ² /litre
Drying times (23 °C, 50 % R.H.):	
Dry to use:	1 hours
Interval between coats:	4 hours
Curing time:	4 weeks
Minimum application temperature:	+10 °C. Best results are achieved when applied at room temperature.

Pretreatment

The substrate must be firm, clean and dry. It is recommended to apply a test coat to check if the result is as expected. Gjøco Sealer can give a deeper color effect, and multiple coats can give a higher gloss.

Directions for use

Gjøco Lime Paint must cure for 24 hours before Gjøco Sealer is applied. Apply 1 coat of Gjøco Sealer. Apply evenly and thinly with a suitable roller or brush. Gjøco Sealer should be applied evenly and rolled out well, to avoid roll stripes and overlap. Using Sealer can make unevenness in the substrate more visible. It is therefore important that the substrate is even and uniform, to get a smooth and nice final result.

Storage	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
Disposal of waste	Liquid paint must not be emptied into sewers or into nature, but delivered to an environmental station. Empty, clean, and dry plastic packaging without a handle can be delivered as plastic waste. 
Other information	Different batch numbers are mixed before use for the final coat to avoid gloss differences. Stir well before use. Gjøco Sealer may yellow when used over alkyd-based paints. Do a test top coat. The color is milky white in the can, but becomes transparent when dry.
Safety	See separate safety data sheet. Read the information on the packaging. EU limit value for this product (cat. A/f): 130 g/l (2010). This product contains: <30 g/l VOC.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information
Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Telephone: +47 712 91 700
E-mail: office@gjoco.no

