

Product datasheet

Gjøco Heftgrunn Vanntynnbar



Gjøco Heftgrunn is a water-thinned acrylic primer with good adhesion to most substrates. The primer is low-odor, dries quickly and has good application properties.

Used on substrates such as building boards, wood, laminate, previously painted surfaces, plastic and tiles in dry rooms.



Revised 08.10.2025

Symbols



Technical data

Type:	Acrylic-based primer
Color:	White
Gloss:	Matte
Application method:	Brush, roller or high-pressure spray. Spraying should be done by professionals.
Thinner/ cleaning agent:	Water
Recommended film thickness, wet:	80-100 micrometer
Recommended film thickness, dry:	35-40 micrometer
Recommended spreading rate:	8-10 m ² /litre
Recommended data for airless spray:	
Nozzle tip:	0.43–0.53 mm (0.017–0.021")
Spray angle degrees:	50°-80°
Pressure at nozzle:	Follow the pump manufacturer's recommendations.
	The choice of nozzle, fan angle, and pressure must be adjusted to the specific spray equipment and substrate.
Drying times (23 °C, 50 % R.H.):	
Dry to use:	1 hours
Interval between coats:	2 hours. Full adhesion is achieved after 4 weeks of thorough curing. Varies with changes in temperature, humidity, ventilation and film thickness.
Minimum application temperature:	+10 °C. Best results are achieved when applied at room temperature.

Pretreatment	<p>The substrate must be clean and dry. Clean with Gjøco Husvask or Gjøco Interiørvask. Follow the instructions on the packaging. Previously painted surfaces, MDF boards and hard, smooth substrates should be mattified with sandpaper and dusted.</p> <p>Building boards may have a surface treatment with wax or the like, check adhesion. When using on plastic, check adhesion by applying a test coat.</p>
Directions for use	<p>Apply evenly and generously. Work quickly and avoid going back to semi-dry paint. On substrates where a smooth and even surface is required, it is recommended to use a suitable brush for touch-ups.</p>
Storage	<p>Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.</p>
Disposal of waste	<p>Liquid paint must not be emptied into sewers or into nature, but delivered to an environmental station. Empty, clean, and dry plastic packaging without a handle can be delivered as plastic waste.</p> <div style="text-align: center;">  </div>
Ecolabelling	<p>Gjøco Heftgrunn is approved by Ecolabelling Norway and meets the requirements for the Nordic ecolabel Svanen.</p> <div style="text-align: center;">  </div>
Other information	<p>Any floatation must be stirred in well before use.</p> <p>Application temperature in air and substrate must be at least +10 °C. Painted surfaces must cure for a minimum of 4 weeks before cleaning with a mild detergent.</p> <p>Stir well before use. Different batch numbers must be mixed before use.</p> <p>Packaging sizes: 0.75 and 2.7 liters</p>
Safety	<p>See separate safety data sheet. Read the information on the packaging.</p> <p>EU limit value for this product (cat. A/a): 30 g/l (2010). This product contains: <3 g/l VOC.</p>

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information

Gjøco AS
 Ørvegen 1160, 6639 Torvikbukt
 Telephone: +47 712 91 700
 E-mail: office@gjoco.no

