

# FDV – Management, Operation and Maintenance

## Gjøco Heftgrunn Vanntynnet



Gjøco Heftgrunn is a water-thinnable acrylic primer with good adhesion to most substrates. The primer has a low odor, dries quickly, and has good application properties.

It is used on substrates such as building panels, wood, laminate, previously painted surfaces, plastic, and tiles in dry rooms.

Revised

07.01.2025

### Usage Instructions

<b>Substrate:</b>	Ensure the surface is clean and dry, with a minimum temperature of +10°C
<b>Application Method:</b>	Brush, roller, or spray. Spraying should be done by professionals.
<b>Thinner:</b>	Water, thinning is generally not necessary.
<b>Storage:</b>	Store and transport upright, dry, frost-free, and out of reach of children.
<b>Transport:</b>	Not classified as hazardous goods under applicable regulations.
<b>Indoor Environment/Emissions</b>	The product emits low emissions.

### Technical and Safety Data

A technical data sheet and safety data sheet (SDS / HSE data sheet) have been prepared for the product. See [www.gjoco.no](http://www.gjoco.no). VOC: The EU limit value for the product (category A/i): 30 g/l (2010). The product contains <3 g/l VOC.

### Maintenance

<b>Cleaning:</b>	For cleaning prior to repainting, it is recommended to use an alkaline cleaning agent such as Gjøco Interiør or Husvask. Follow the product instructions. Newly painted surfaces should not be washed until after 4 weeks. Use microfiber cloths with clean water or mild soapy water. The cleaning water temperature should not exceed +40°C, and the pH should not exceed 9. The use of abrasive cleaning agents may damage the surface. Cleaning should be carried out in a way that avoids streaks and performed with discretion. The paint film wears faster under heavy cleaning loads.
------------------	---

**Intervals:**

The paint film is affected by mechanical impact and wears according to the level of stress. Maintenance intervals will therefore vary based on need.

**Waste Management**

Liquid paint must not be poured into sewage drains or into the environment, but should be delivered to an approved hazardous waste disposal facility. Empty, clean, and dry plastic packaging without handles can be disposed of as plastic waste.



**Repairs/Damage**

Repairs and damages should be addressed using the same type of product. If other products are used, it must be documented that they are of the same type previously applied. Repairs should be carried out in a way that does not deviate from previous treatments. For repainting or color changes, it is recommended to use the same product as previously applied. Contact your dealer or a painting company for assistance.

**Environmental labeling:**

The product is approved by Miljømerking Norge and meets the requirements for the Swan environmental label.



**Treated Surface/Type of Substrate:**

**Painted in Color:**

**Color Name:**

**NCS:**

**Batch Number:**

**Painting Performed By:**

**Date:**

**Signature:**

The information in this data sheet is based on laboratory tests and practical experience. As our products are semi-finished goods, and usage conditions often fall outside our control, we only guarantee the product's quality. Products are delivered under our general terms of sale, delivery, and service unless otherwise agreed in writing. Minor product changes and data updates may occur without notice. This data sheet replaces previous editions and is automatically invalidated five years after its issue date.

**Contact Information**

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukta  
Phone: +47 712 91 700  
Email: office@gjoco.no

