

FDV – Management, Operation and Maintenance

Gjøco Kvist og Sperregrunn



Gjøco Kvist and Barrier Primer is a water-thinned, sealing primer for indoor use, based on modified epoxy resin. The primer has excellent application properties, making it easy to apply. It prevents bleeding from knots, yellowed paneling, nicotine, and soot. Gjøco Kvist and Barrier Primer is specifically designed for new and fresh pine paneling and other panels with knot bleed-through. Please note that knot bleed-through is a natural phenomenon that may appear over time.

Revised 07.01.2025

Usage Instructions	Substrate:	Ensure the surface is clean and dry, with a minimum temperature of +15°C
	Application Method:	Brush or foam roller designed for lacquer.
	Thinner:	Water. The lacquer generally does not require thinning.
	Storage:	Store and transport upright, dry, frost-free, and out of reach of children.
	Transport:	Not classified as hazardous goods under applicable regulations.
	Indoor Environment/Emissions	The product emits low emissions.

Technical and Safety Data A technical data sheet and safety data sheet (SDS / HSE data sheet) have been prepared for the product. See www.gjoco.no. VOC: The EU limit value for the product (category A/i): 30 g/l (2010). The product contains <20 g/l VOC.

Maintenance	Cleaning:	For cleaning prior to repainting, it is recommended to use an alkaline cleaning agent such as Gjøco Interiørvask or Husvask. Follow the product instructions. Newly painted surfaces should not be washed until after 4 weeks. Use microfiber cloths with clean water or mild soapy water. The cleaning water temperature should not exceed +40°C, and the pH should not exceed 9. The use of abrasive cleaning agents may damage the surface. Cleaning should be carried out in a way that avoids streaks and performed with discretion. The paint film wears faster under heavy cleaning loads.
	Intervals:	The paint film is affected by mechanical impact and wears according to the level of stress. Maintenance intervals will therefore vary based on need.

Waste Management

The product is classified as hazardous waste and must be delivered to an approved hazardous waste disposal facility. The product must not be poured into the environment, sewage, or water. Empty, clean, and dry plastic packaging without handles can be disposed of as plastic waste. Refer to applicable regulations for hazardous waste.



Repairs/Damage

Repairs and damages should be addressed using the same type of product. If other products are used, it must be documented that they are of the same type previously applied. Repairs should be carried out in a way that does not deviate from previous treatments. For repainting or color changes, it is recommended to use the same product as previously applied. Contact your dealer or a painting company for assistance.

Treated Surface/Type of Substrate:

Painted in Color:

Color Name:

NCS:

Batch Number:

Painting Performed By:

Date:

Signature:

The information in this data sheet is based on laboratory tests and practical experience. As our products are semi-finished goods, and usage conditions often fall outside our control, we only guarantee the product's quality. Products are delivered under our general terms of sale, delivery, and service unless otherwise agreed in writing. Minor product changes and data updates may occur without notice. This data sheet replaces previous editions and is automatically invalidated five years after its issue date.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Phone: +47 712 91 700
Email: office@gjoco.no

