

Product datasheet

Kvist og Sperregrunn



Gjøco Kvist og Sperregrunn is a water-based sealer primer for indoor use, made from modified epoxy resin. The primer has good application properties, making it easy to brush on. It limits the bleeding from knots, yellowed panels, nicotine, and soot. Gjøco Kvist og Sperregrunn is specifically designed for new and fresh pine panels and other panels with knot bleeding. Please note that bleeding from knots is a natural phenomenon that may appear over time.

Revised 04.03.2025

Symbols




Technical data

Type:	Based on modified epoxy resin
Color:	White base
Gloss:	Matte 4-6
Density:	1.3 kg/l
Application Method:	Brush, roller, or high-pressure sprayer. Spraying should be done by professionals.
Thinner/ cleaning agent:	Water. The product should not be thinned.
Recommended Coverage:	8-10 m ² /liter, depending on the substrate.
Recommended Data for High-Pressure Sprayer:	
Nozzle Size:	0.53 mm / 0.021"
Fan Angle:	65°-80°
Paint Pressure:	Min. 150 kg/cm ²
Drying Time (23°C, 50% R.H.):	
Dust Dry:	1 hour
Re-coat Interval, Minimum:	6 hours. May vary with changes in temperature, humidity, ventilation, and film thickness.
Minimum Application Temperature:	+15°C. Best results are achieved when applied at room temperature.
Corrosion:	All equipment that comes in contact with Gjøco Kvist og Sperregrunn must be made of stainless steel, otherwise, the metal may corrode.

Surface Preparation

The substrate must be clean and dry. Clean with Gjøco Interiørvask or Gjøco Gulvrens. Follow the instructions on the packaging. Previously painted surfaces, MDF boards, and hard, smooth substrates should be sanded with sandpaper and dusted off.

Usage Instructions	For use on lightly discolored and yellowed surfaces, apply 1-2 coats of Gjøco Kvist og Sperregrunn. For blocking knot bleed and on heavily discolored surfaces, apply 2 coats. On surfaces that require a smooth and even finish, it is recommended to use a suitable brush for touch-ups. When using on tiles, plastic, and other smooth surfaces, check adhesion by applying a test coat.
Cleaning of Painting Equipment	All painting equipment must be clean and free from other paint residues before use. Clean all equipment thoroughly with clean water immediately after use, especially when using a high-pressure sprayer. Run large amounts of water through the sprayer before and after use to ensure it is completely clean. Gjøco Kvist og Sperregrunn can cause corrosion on metal that is not stainless steel.
Storage	Tightly seal the lid when storing paint to prevent spillage and drying out. The paint should be transported and stored upright, in a dry and frost-free environment.
Disposal of waste	Liquid paint and wash water should not be disposed of in sewage drains or nature but should be taken to a recycling station. Empty, clean, and dry plastic packaging without a handle can be disposed of as plastic waste.
	
Other information	<p>Stir well before use. Tightly seal the lid when storing the paint to prevent spillage and drying out. Liquid paint should not be emptied into drains but should be delivered to a recycling station. Store and transport standing, in a dry and frost-free environment. Can cause corrosion on metal that is not stainless steel.</p> <p>For more detailed information, refer to the safety and technical datasheets. To avoid cracking along panel joints due to changes in humidity, it is recommended that the panels be treated before installation. Alternatively, the panels can be treated after winter when humidity is typically at its lowest.</p> <p>Packaging Size: 3 liters</p>
Safety	See separate safety data sheet. Read the information on the packaging. EU limit for this product (cat. A/g): 30 g/l (2010). This product contains: <20 g/l VOC.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information

Gjøco AS
 Ørvegen 1160, 6639 Torvikbukt, Norway
 Telephone: +47 712 91 700
 E-mail: office@gjoco.no

