

Product data sheet

Gjøco Sylothix



Gjøco Sylothix is used as an thickening agent in solvent-free epoxy products such as GjøcoPoxy SL or GjøcoPoxy BP Concrete Primer for use as a filler compound. The filler is used for repairing surface damage and forming coves in concrete and masonry substrates.

Revised:

28.10.2025

Symbols



Technical data

Type:

Fiber with thickening properties.

Applications

Used for filling surface damage and forming coves in concrete and masonry substrates.

Add to GjøcoPoxy SL or GjøcoPoxy BP Concrete Primer until a mashed-potato-like consistency is achieved. First, mix part A and part B thoroughly with an electric mixer. Then add Sylothix and stir well. Apply to damaged areas and coves using a spatula. The surface can be treated with other epoxy products immediately afterward.

Application method: Add to solvent-free epoxy products such as GjøcoPoxy SL or GjøcoPoxy BP Concrete Primer until the desired mashed-potato-like consistency is reached. First, mix part A and part B thoroughly with an electric mixer. Then add Sylothix and mix well. Increase the amount of Sylothix until the mixture reaches the desired consistency (approx. 6% by weight). For small repair jobs, it is advisable to weigh out smaller amounts to ensure easier incorporation of Sylothix. The surface can be treated with other epoxy products immediately afterward.

Storage:

The packaging must be kept tightly closed and stored in a dry place at a consistent temperature. The product should be transported and stored upright, in a dry and frost-free environment.

Waste Disposal:

The product must not be poured into drains or released into the environment, but should be delivered to a recycling or disposal facility. Empty, clean, and dry plastic packaging without a handle can be disposed of as plastic waste.



Additional information:

Packaging sizes – various.

Safety

Refer to the separate safety data sheet. Read the information on the packaging.

The information in this data sheet is based on laboratory tests and practical experience. Since the conditions under which the products are used are often beyond our control, we can only guarantee the quality of the product itself. The products are supplied in accordance with our general terms of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint should be considered a semi-finished product, and the result depends on surface preparation, temperature, application, type of substrate, etc. This data sheet supersedes all previous editions.

Contact Information

Gjøco AS, Galterud
Sagmoen 100, NO-2223 Galterud, Norway
Phone: +47 712 91 700
Email: office@gjoco.no

