



FDV - Management, Operation and Maintenance

GjøcoPur TL Matt



GjøcoPur TL Matt is a solvent-free, matte polyurethane topcoat with good wear resistance, scratch resistance, and UV stability. It is intended as a topcoat for use on concrete, wood, and thermoset resin. The product can be applied directly to concrete and can be tinted to the desired color. GjøcoPur TL Matt can be used as either a single-component or two-component system.

Revised

14.10.2025

Application Instructions	Substrate:	The substrate must be solid, clean, dry, free of dust and grease, and have a temperature of at least +12 °C for both substrate and air, and at least 3 °C above the current dew point.
	Application method:	Roller or airless spray.
	Thinner:	The product must not be thinned.
	Storage:	The product must be stored in accordance with national regulations. The packaging must be kept tightly closed and stored in a dry place at a stable temperature. The product must be transported and stored upright, dry, and frost-free.
	Indoor environment / emissions:	The product has low emissions.
Product Data Sheet and Safety Data Sheet	A product data sheet and safety data sheet (SDS) have been prepared for the product. See www.gjoco.no .	
Maintenance	Cleaning:	Before repainting, Gjøco Gulv og Panelrens is recommended. Follow the instructions on the product. When applying a new coat of varnish, the substrate should be lightly sanded to ensure adhesion. See the product data sheet for additional information.
	Interval:	The paint film is affected by mechanical stress and wears depending on the level of use. Maintenance intervals will therefore vary according to need.

Waste Management

Liquid thermoset resin must not be poured into drains or released into the environment but should be delivered to a recycling or waste collection station. Cured thermoset resin can be disposed of at waste collection stations as residual waste, but it is recommended to contact the local facility for specific guidance, as regulations may vary locally.

**Repairs / Damage**

Repairs and damage should be remedied using the same type of product. If other products are used, it must be documented that they are of the same type as previously applied. When repairing damage, the work should be carried out so that it does not differ from previous treatments. For repainting or color changes, it is recommended to use the same product as before. Contact the supplier or painting company.

Treated Surface / Type of Substrate:

.....

Painted in Color:

Color Name:

.....

NCS:

.....

Batch Number:

.....

Painting Work Performed By:

.....

Date:

.....

Signature:

.....

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished, and since the conditions under which they are used are often beyond our control, we can only guarantee the quality of the product itself. The products are supplied in accordance with our general terms of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to make minor product modifications and to change the specified data without prior notice. This data sheet replaces previous editions and is automatically void five years after the date of issue.

Contact Information

Gjøco AS, Galterud
Sagmoen 100, NO-2223 Galterud, Norway
Phone: +47 712 91 700
Email: office@gjoco.no

