

Product Data Sheet

Proff Excellent 30



Gjøco Proff Excellent 30 is a low-odor, durable, water-thinned acrylic paint designed for indoor use. The paint offers excellent adhesion and coverage. It is non-yellowing and provides a hard, washable, and highly wear-resistant surface. Ideal for intermediate and topcoats on doors, windows, frames, moldings, furniture, and panels.

Revised

05.12.2024

Symbols



Technical Data



Type:	Water-thinnable pure acrylic paint
Color:	White base, A, B, and C
Gloss:	Available in gloss level 30
Density:	Approx. 1.1–1.3 kg/l
Solids:	Approx. 34–36% by volume
Application Methods:	Brush, roller, or spray. Spraying should be performed by professionals
Thinner / Cleaning Agent:	Water
Recommended Coverage:	Approx. 8 m ² /liter, depending on the substrate
Drying Time (23°C, 50% RH):	
Dust-dry:	1 hour
Minimum recoat interval:	4 hours
Fully dry for use:	24 hours. Full adhesion achieved after 4 weeks of curing. Varies with temperature, humidity, ventilation, and film thickness
Minimum Application Temperature:	+10°C. Best results achieved when applied at room temperature

Surface Preparation

Ensure the surface is firm, clean, and dry. Clean with Gjøco Interiørvask and rinse thoroughly with clean water. Previously painted surfaces, MDF panels, and hard, smooth substrates should be sanded to a matte finish and primed with Gjøco Proff Heft. Discolored surfaces should be primed with Gjøco Proff Isolør to prevent bleed-through.

Application

Gjøco Proff Excellent 30 is ready to use and generally does not require thinning. Apply evenly and generously with appropriate painting tools. Apply 1–2 coats as

	needed. On absorbent surfaces, additional coats may be necessary to avoid streaks. To ensure proper flow, avoid reworking partially dried paint.
Colors	Use the same batch number for a single coat on the same surface to prevent gloss and color variations. If necessary, mix different batch numbers before use. Note that color differences can occur if paint is mixed on different machines or at different times. Be mindful of this if additional paint is required for the same project later.
Environmental Certification	Gjøco Proff Excellent 30 is approved by Miljømerking Norge and meets the requirements of the Swan Ecolabel. 
Storage	Seal the lid tightly during storage to prevent spillage and drying out. Paint should be transported, stored, and kept upright in a dry and frost-free environment.
Waste Management	Do not pour liquid paint or wash water into drains or nature. Dispose of it at an approved hazardous waste facility. Empty, clean, and dry plastic containers  without handles can be disposed of as plastic waste.
Additional Information	Stir thoroughly before use. Available packaging sizes: 2.7 L and 9 L.
Safety	Refer to the safety data sheet and read the information on the packaging. EU limit value for this product (category A/d): 130 g/l (2010). This product contains: <75 g/l VOC.

The information provided in this datasheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and since the conditions under which they are used are often beyond our control, we can only guarantee the quality of the product itself. Products are supplied in accordance with our general terms for sales, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product adjustments and update the stated data without prior notice. This datasheet supersedes previous editions.

Contact Information **Gjøco AS**
Ørvegen 1160, 6639 Torvikbukt
Phone: +47 712 91 700
Email: office@gjoco.no

