

Product Data Sheet

Proff Heft



Gjøco Proff Heft is a water-based acrylic primer with excellent adhesion to most surfaces. The primer is low-odor, dries quickly, and provides good application properties. It is suitable for substrates such as building boards, woodwork, laminate, and previously painted surfaces in dry rooms.

Revised 05.12.2024

Symbols



Technical Data

Type:	Acrylic-based primer
Color:	White
Gloss:	Matte
Density:	Approx. 1.4 kg/l
Solids:	Approx. 34–36% by volume
Application Methods:	Brush, roller, or spray. Spraying should be performed by professionals
Thinner / Cleaning Agent:	Water
Recommended Coverage:	7 - 10 m ² /liter, depending on the substrate
Recommended Data for High-Pressure Sprayer:	
Nozzle:	0.021", 0.53 mm
Fan Angle:	65-80°
Paint Pressure:	150 kg/cm ²
Drying Time (23°C, 50% RH):	
Dust-dry:	1 hour
Minimum Repainting Interval:	2 hours. Full adhesion is achieved after 4 weeks of curing. This may vary with changes in temperature, humidity, ventilation, and film thickness.
Minimum Application Temperature:	+10°C. Best results achieved when applied at room temperature

Preparation

The surface must be clean and dry. Clean with Gjøco Husvask or Gjøco Interiørvask, following the instructions on the packaging. Previously painted surfaces, MDF boards, and hard, smooth substrates should be sanded and

	dusted off. Building boards may have been treated with wax or similar products—check adhesion.
Application	Gjøco Proff Heft is ready to use and should normally not be thinned. Apply evenly and generously. Work quickly and avoid going back over half-dried paint. For substrates requiring a smooth and even finish, it is recommended to use an appropriate brush for touch-ups.
Colors	Use the same batch number for a single coat on the same surface to prevent gloss and color variations. If necessary, mix different batch numbers before use. Note that color differences can occur if paint is mixed on different machines or at different times. Be mindful of this if additional paint is required for the same project later.
Environmental Certification	Gjøco Proff Heft is approved by Miljømerking Norge and meets the criteria for the Swan environmental label. 
Storage	Seal the lid tightly when storing to prevent spills and drying. The paint should be transported, stored, and kept upright in a dry and frost-free environment.
Waste Management	Liquid paint and wash water should not be poured into drains or nature but must be delivered to an approved hazardous waste collection point. Empty, clean, and dry plastic packaging without handles can be disposed of as plastic waste. 
Additional Information	Stir thoroughly before use. Available packaging sizes: 3 L
Safety	See the safety data sheet for details. Read the information on the packaging. EU limit value for this product (cat. A/a): 30 g/l (2010). This product contains: <3 g/l VOC.

The information provided in this datasheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and since the conditions under which they are used are often beyond our control, we can only guarantee the quality of the product itself. Products are supplied in accordance with our general terms for sales, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product adjustments and update the stated data without prior notice. This datasheet supersedes previous editions.

Contact Information
Gjøco AS
 Ørvegen 1160, 6639 Torvikbukt
 Phone: +47 712 91 700
 Email: office@gjoco.no

