

# FDV – Management, Operation and Maintenance

## Gjøco Proff Isolér



Gjøco Proff Isolér is a water-borne primer for blocking and isolating stains such as soot, nicotine, and other discolorations. It helps prevent resin bleed-through from knots. Can be used on most substrates such as wood paneling, building boards, glass fiber fabric, wallpaper, plasterboards, old plaster, and concrete, etc. Should not be used on new concrete.

Revised

12.03.2026

<b>Usage Instructions</b>	<b>Surface:</b>	The surface must be clean and dry, with a minimum temperature of +5°C.
	<b>Application Method:</b>	Brush, roller, or spray. Spraying should be done by professionals.
	<b>Thinner:</b>	Water; thinning is usually not necessary.
	<b>Storage:</b>	Store and transport upright, in a dry and frost-free environment, and out of reach of children.
	<b>Transport:</b>	Not classified as hazardous goods under applicable regulations.
	<b>Indoor Environment/Emissions</b>	The product emits a mild vapor.

**Technical and Safety Data**

A technical data sheet and safety data sheet (SDS / HSE data sheet) have been prepared for the product. See [www.gjoco.no](http://www.gjoco.no). VOC: EU limit value for this product (cat. A/g): 30 g/l (2010). The product contains <30 g/l VOC.

**Maintenance**

**Cleaning:** For cleaning before repainting, it is recommended to use an alkaline cleaning agent such as Gjøco Interiørvask, Gjøco Gulv- og panelrens, or Husvask. Follow the instructions for use on the product. Newly painted surfaces should not be washed until after 3–4 weeks. It is recommended to use microfiber cloths with clean water or mild soapy water. The temperature of the washing water should not exceed +40 °C, and the pH should not exceed 9. The use of cleaning agents containing abrasives may damage the surface. Cleaning should be carried out in a way that does not leave streaks. Cleaning should be performed as

needed. The paint film will wear faster under heavy cleaning.

**Intervals:**

The paint film is affected by mechanical stress and will wear according to the level of use. The maintenance interval will therefore vary depending on the need.

**Waste Management**

Liquid paint should not be disposed of in sewage systems or nature, but should be delivered to an approved hazardous waste facility. Empty, clean, and dry plastic packaging without handles can be delivered as plastic waste.



**Repairs/Damage**

Repairs and damage should be remedied using the same type of product. Documentation must confirm that the same type of product was previously used if different products are considered. Repairs should be carried out to match the original treatment. For repainting or color changes, it is recommended to use the same product as before. Contact your dealer or a painting professional for assistance.

**Environmental Labeling:**

The product is approved by the Nordic Ecolabel (Svanen) and meets the requirements for the Svanen environmental label.



**Treated Surface/Type of Substrate:**

.....

**Painted in Color:**

**Color Name:**

**NCS:**

**Batch Number:**

**Painting Performed By:**

**Date:**

**Signature:**

.....

.....

.....

The information in this data sheet is based on laboratory tests and practical experience. As our products are semi-finished goods, and usage conditions often fall outside our control, we only guarantee the product's quality. Products are delivered under our general terms of sale, delivery, and service unless otherwise agreed in writing. Minor product changes and data updates may occur without notice. This data sheet replaces previous editions and is automatically invalidated five years after its issue date.

**Contact Information**

**Gjøco AS**

Ørvegen 1160, 6639 Torvikbukt, Norway

Phone: +47 712 91 700

Email: office@gjoco.no

