

## Product datasheet

# Gjøco Proff Solid



Gjøco Proff Solid is a water-resistant, solvent-free PVA dispersion paint with low odour for indoor use in dry rooms. Gjøco Proff Solid is used as intermediate and top coat on building boards, overpaintable wallpaper, woven fabric, plaster, concrete and putty, previously painted surfaces etc.

Revised 04.03.2025

Symbols





### Technical data

Type:	PVA dispersion
Color:	White + A, B, C, tinted by using Gjøcomix.
Gloss:	5, 7, 10 and 20
Specific gravity:	Approx. 1.4 kg/l (White base)
Solid content:	Approx. 40 volume%
Application method:	Roller, brush or airless spray.
Thinner/ cleaning agent:	Water and a suitable cleaning agent.
Recommended spreading rate:	7-10 m <sup>2</sup> /liter, depending on surface.
Guiding data for airless spray:	
Nozzle:	0.53 mm (0.021")
Spray angel:	65° - 80°
Pressure at nozzle:	Min. 15 MPa (Min. 150 kg/cm <sup>2</sup> )
Drying times (23 °C, 50 % R.H.):	Drying time deviates at changes in temperature, air humidity, air circulation and film thickness.
Dust dry:	1 hour
Interval between coats:	3 hours
Cured:	4 weeks
Minimum application temperature:	+5 °C. Best results are obtained by application at room temperature.

### Pretreatment

The surface must be clean and dry. Clean with Gjøco Husvask or Gjøco Interiørvask. Rinse with water. Sand down previously painted, old glossy/semi glossy paint with suitable abrasive paper and remove dust and primed with Gjøco Proff Heft.

<b>Directions for use</b>	The product is ready for use and does not need thinner. Textile wall covering to be primed with a suitable primer. Surfaces discoloured by soot, nicotine etc. should be primed with Gjøco Sperregrunn / Gjøco Proff Isolør. Use 2 coats as topcoat with Gjøco Proff Solid. 3 coats on absorbant, porous surfaces can be recommended to avoid discolouring.
<b>Storage</b>	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
<b>Eco labelling</b>	Gjøco Proff Solid is approved by Ecolabelling Norway and meets the requirements for the Nordic Ecolabel. 
<b>Disposal of waste</b>	Liquid oil must not be emptied into sewers or into nature, but delivered to an environmental station. Empty, clean, and dry plastic packaging without a handle can be delivered as plastic waste. 
<b>Safety</b>	See separate safety data sheet. Read the information on the packaging. EU limit value for this product (cat. A/a): 30 g/l (2010). This product contains: <30 g/l VOC.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

**Contact information**      **Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukt, Norway  
Telephone: +47 712 91 700  
E-mail: [office@gjoco.no](mailto:office@gjoco.no)

