

Product Data Sheet

Proff Tak og Loft Primadekk



Gjøco Proff Isolér is a water-based primer designed for sealing and isolating stains such as soot, nicotine, and other pigments. It prevents resin bleed-through from knots in wood. It can be used on various surfaces such as paneling, building boards, fiberglass, wallpaper, plasterboard, old plaster, and concrete, among others. However, it should not be used on new concrete.

Revised 12.12.2024

Symbols



Technical Data

Type:	PVA dispersion paint
Color:	S0500N
Gloss:	Matte (1–3)
Density:	Approximately 1.38 kg/l
Solids by volume	Approximately 40%
Application Methods:	Brush, roller, or spray. Spraying should be performed by professionals
Thinner / Cleaning Agent:	Water
Recommended Coverage:	8–10 m ² /liter, depending on the substrate
Recommended Data for High-Pressure Spraying:	
Nozzle:	0.021" (0.53 mm)
Fan Angle:	65–80°
Paint Pressure:	150 kg/cm ²
Drying Time (23 °C, 50% RH):	
Dust-Dry:	1 hour
Recoat Interval (minimum):	2 hours. Full adhesion is achieved after 4 weeks of curing. Drying times may vary depending on temperature, humidity, ventilation, and film thickness.
Minimum Application Temperature:	+5°C. Optimal results are achieved when applied at room temperature.

Preparation

The surface should be solid, clean, and dry. Clean with Gjøco Husvask or Gjøco Interiørvask, and rinse thoroughly with clean water. Smooth surfaces should be sanded down. Discolored areas should be primed with Gjøco Proff Isolér to

prevent stains from showing through. Untreated masonry, previously limewashed surfaces, and highly chalking substrates should be scraped, brushed, and primed with Gjøco Primer for masonry and concrete before applying Gjøco Proff Tak og Loft Primadekk.

Application

Gjøco Proff Tak og Loft Primadekk is ready for use and should normally not be thinned. Apply 1–2 coats as needed. For absorbent surfaces, additional coats may be necessary to avoid streaks.

Environmental Certification

Gjøco Proff Tak og Loft Primadekk is approved by the Norwegian Ecolabelling Foundation and meets the requirements for the Nordic Swan eco-label.

**Storage**

Seal the lid tightly when storing the paint to prevent spills and drying out. The paint should be transported, stored, and kept upright, in dry conditions, and frost-free.

Waste Management

Liquid paint and wash water must not be poured into sewers or nature but should be delivered to an approved hazardous waste facility. Empty, clean, and dry plastic containers without handles can be disposed of as plastic waste.

**Additional Information**

Stir thoroughly before use. Packaging sizes: 9 L.

Safety

Refer to the safety data sheet. Read the information on the packaging. EU limit value for this product (cat. A/a): 30 g/l (2010). This product contains: <10 g/l VOC.

The information provided in this datasheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and since the conditions under which they are used are often beyond our control, we can only guarantee the quality of the product itself. Products are supplied in accordance with our general terms for sales, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product adjustments and update the stated data without prior notice. This datasheet supersedes previous editions.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukta
Phone: +47 712 91 700
Email: office@gjoco.no

