



FDV – Management, Operation and Maintenance

Proff Tak og Loft



Gjøco Proff Tak og Loft is a low-odor, solvent-free, water-based, and reflection-free PVA dispersion paint for indoor use in dry rooms. It is used as both a primer and topcoat on ceilings made of building boards, plaster, concrete, fabric, and sanded filler.

Revised 11.03.2025

Usage Instructions	Surface:	The surface must be clean and dry, with a minimum temperature of +5°C.
	Application Method:	Brush, roller, or spray. Spraying should be done by professionals.
	Thinner:	Water; thinning is usually not necessary.
	Storage:	Store and transport upright, in a dry and frost-free environment, and out of reach of children.
	Transport:	Not classified as hazardous goods under applicable regulations.
	Indoor Environment/Emissions	The product has low emissions.

Technical and Safety Data A technical data sheet and safety data sheet (SDS / HSE data sheet) have been prepared for the product. See www.gjoco.no. VOC: EU limit value for this product (cat. A/g): 30 g/l (2010). The product contains <10 g/l VOC.

Maintenance	Cleaning:	For cleaning before repainting, it is recommended to use an alkaline cleaning agent such as Gjøco Interiørvask or Husvask. Follow the instructions on the product. Newly painted surfaces should not be washed for 3–4 weeks. Use microfiber cloths with clean water or a mild soapy solution. The water temperature should not exceed +40°C, and the pH should not exceed 9. The use of cleaning agents with abrasives can damage the surface. Cleaning should be done in a way that prevents streaking. Cleaning is performed as needed. The paint film wears out faster with frequent cleaning.
	Intervals:	The paint film is affected by mechanical wear and will deteriorate depending on the level of exposure. The maintenance interval will therefore vary based on need.

Waste Management

Liquid paint must not be disposed of in sewage systems or nature but should be delivered to an approved hazardous waste facility. Empty, clean, and dry plastic packaging without a handle can be disposed of as plastic waste.



Repairs/Damage

Repairs and damage should be fixed using the same type of product. If other products are used, documentation must confirm that they are of the same type as previously used. Repairs should be carried out in a way that does not deviate from previous treatments. When repainting or changing color, it is recommended to use the same product as before. Contact your dealer or a painting company for advice.

Environmental Labeling:

The product is approved by the Nordic Ecolabel (Svanen) and meets the requirements for the Svanen environmental label.



Treated Surface/Type of Substrate:

Painted in Color:

Color Name:

NCS:

Batch Number:

Painting Performed By:

Date:

Signature:

The information in this data sheet is based on laboratory tests and practical experience. As our products are semi-finished goods, and usage conditions often fall outside our control, we only guarantee the product's quality. Products are delivered under our general terms of sale, delivery, and service unless otherwise agreed in writing. Minor product changes and data updates may occur without notice. This data sheet replaces previous editions and is automatically invalidated five years after its issue date.

Contact Information

Gjøco AS

Ørvegen 1160, 6639 Torvikbukt, Norway

Phone: +47 712 91 700

Email: office@gjoco.no

