

Product datasheet

Gjøco Proff Tak/Loft



Gjøco Proff Tak/Loft is a low odor, solvent-free, water thinned and reflex-free PVA dispersion paint for indoor use in dry rooms. Used as primer and topcoat in roofs of building boards, plaster, concrete, tissue and sand putty.

Revised 04.03.2025

Symbols





Technical data

Type:	Pure PVA paint
Color:	White can be broken in bright colors.
Gloss:	Velvet
Specific gravity:	Approx. 1.37 kg/l
Solid content:	Approx. 55 volume%
Application method:	Roller, brush or airless spray.
Thinner/ cleaning agent:	Water
Film thickness, wet:	120 micrometers
Film thickness, dry:	59 micrometers
Recommended spreading rate:	8-10 m ² /liter
Guiding data for airless spray:	
Nozzle:	0.53 mm (0.021")
Spray angel:	65° - 80°
Pressure at nozzle:	Min. 150 kg/cm ²
Drying times (23 °C, 50 % R.H.):	Drying time deviates at changes in temperature, air humidity, air circulation and film thickness.
Dust dry:	1 hour
Interval between coats:	2 hours
Minimum application temperature:	+10 °C. Best results are obtained by application at room temperature.

Pretreatment

The surface must be clean and dry. Clean with Gjøco Husvask and rinse well with clean water. Smooth surfaces are dulled with sandpaper. Stained surfaces are primed with Gjøco Proff Isoler to prevent breakdown. Untreated masonry,

	previously limed and heavily contaminated substrates are scraped, brushed, and sewn with Gjøco Murseis or Mineralprimer before applying Gjøco Proff Tak/Loft.
Directions for use	Gjøco Proff Tak/Loft is ready for use and must not be thinned. Apply 1-2 coats as needed. On suction surfaces, several coats may be required to avoid stains.
Storage	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
Eco labelling	Gjøco Proff Tak/Loft is approved by Ecolabelling Norway and meets the requirements for the Nordic Ecolabel. 
Disposal of waste	Liquid oil must not be emptied into sewers or into nature, but delivered to an environmental station. Empty, clean, and dry plastic packaging without a handle can be delivered as plastic waste. 
Safety	See separate safety data sheet. Read the information on the packaging. EU limit value for this product (cat. A/a): 30 g/l (2010). This product contains: <10 g/l VOC.
Other information	Application temperature in air and substrate must be at least +10°C. Stir well before use. Different production numbers are mixed before use. Package size: 9 liters

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information
Gjøco AS
 Ørvegen 1160, 6639 Torvikbukt
 Telephone: +47 712 91 700
 E-mail: office@gjoco.no

