



FDV – Management, Operation and Maintenance Proff Uno



Gjøco Proff Uno is a low-odor, water-based pure acrylic paint for indoor use. It provides good coverage and creates a durable surface that is easy to keep clean. It is ideal for use as a wall paint. It can be applied to building boards, plaster, concrete, fiberglass wallpaper, environmental wallpaper, previously painted surfaces, etc.

Revised

09.04.2026

Usage Instructions	Surface:	The surface must be clean and dry, with a minimum temperature of +5°C.
	Application Method:	Brush, roller, or spray. Spraying should be done by professionals.
	Thinner:	Water; thinning is usually not necessary.
	Storage:	Store and transport upright, in a dry and frost-free environment, and out of reach of children.
	Transport:	Not classified as hazardous goods under applicable regulations.
	Indoor Environment/Emissions	The product has low emissions.
Technical and Safety Data	A technical data sheet and safety data sheet (SDS / HSE data sheet) have been prepared for the product. See www.gjoco.no . VOC: EU limit value for this product (cat. A/g): 30 g/l (2010). The product contains <1 g/l VOC.	
Maintenance	Cleaning:	For cleaning before repainting, it is recommended to use an alkaline cleaning agent such as Gjøco Interiørvask or Husvask. Follow the instructions on the product. Newly painted surfaces should not be washed for 3–4 weeks. Use microfiber cloths with clean water or a mild soapy solution. The water temperature should not exceed +40°C, and the pH should not exceed 9. The use of cleaning agents with abrasives can damage the surface. Cleaning should be done in a way that prevents streaking. Cleaning is performed as needed. The paint film wears out faster with frequent cleaning.
	Intervals:	The paint film is affected by mechanical wear and will deteriorate depending on the level of exposure. The maintenance interval will therefore vary based on need.

Waste Management

Liquid paint must not be disposed of in sewage systems or nature but should be delivered to an approved hazardous waste facility. Empty, clean, and dry plastic packaging without a handle can be disposed of as plastic waste.



Repairs/Damage

Repairs and damage should be fixed using the same type of product. If other products are used, documentation must confirm that they are of the same type as previously used. Repairs should be carried out in a way that does not deviate from previous treatments. When repainting or changing color, it is recommended to use the same product as before. Contact your dealer or a painting company for advice.

Eco-labeling

The product is approved by the Nordic Ecolabel (Svanen) and meets the requirements for the Svanen environmental label.



BREEAM-NOR v6.1:

- HEA02: The product complies with VOC content requirements in accordance with EU Directive 2004/42/EC and emission requirements tested in accordance with the ISO 16000 and ISO 11890 series.
- MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet.

Treated Surface/Type of Substrate:

.....

Painted in Color:

Color Name:

.....

NCS:

.....

Batch Number:

.....

Painting Performed By:

.....

Date:

.....

Signature:

.....

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

Contact Information

Gjøco AS

Ørvegen 1160, 6639 Torvikbukta, Norway

Phone: +47 712 91 700

Email: office@gjoco.no

