

Product data sheet

Gjøco Møbel- og kjøkkenbenkolje



Gjøco Møbel- og kjøkkenbenkolje is a special oil for indoor use on wooden surfaces such as kitchen benches, work surfaces and wooden furniture in the kitchen, bathroom and living room. This product provides good protection against moisture, dirt, and grease. Can be blended in different colors. Contains no toxic substances and is therefore suitable for treating surfaces that will be in direct contact with food.

Revised

23.10.2025

Symbols



Technical data

Type:	Water-thinned oil
Color:	Colorless
Specific gravity:	1.01 kg/l
Viscosity:	200 cP
Application method:	Lacquer brush or sponge.
Thinner/ cleaning agent:	Water
Recommended spreading rate:	15 m ² /liter per coat
Drying times (23 °C, 50 % R.H.):	
Interval between coats:	2 hours
Dry to use:	24 hours
Cured:	Approx. 7 days
Minimum application temperature:	+15 °C.

Pretreatment

The surface must be clean and dry. Remove grease, wax and soap residue with Gjøco Gulv- og panelrens or Gjøco Interiørrens. It also must be done for new untreated wood. The surface is sanded down with abrasive paper no. 150-180. Vacuum and then dry over the surface with a microfiber cloth. Previously oiled surfaces with deep scratches and damages should be sanded down to bare wood.

Directions for use

It is recommended that the color and finish be tested with a test coat, to see that the result is as desired. The absorbency of the wood will affect the result, as will the color and number of coats. The more coats, the stronger the color. Apply Gjøco Møbel- og kjøkkenbenkolje with a lacquer brush or sponge in the direction of the grain. The type of application tool can produce different finishes; take test

smears. Let dry for approx. 2 hours. Then apply another coat and let it dry for a day before putting the surface into use. If necessary, polish the surface with a cloth.

Always use the same batch number on the same surface to avoid gloss differences. Stir well before and during use. Do not expose the surface to strong stress (water spills, shocks, etc.) in the first week after treatment. Water spillage etc. dried up immediately. Contact with acidic and fatty products is limited to two hours.

Storage

Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.

Disposal of waste

Liquid oil must not be emptied into sewers or into nature, but delivered to an environmental station. Empty, clean, and dry plastic packaging without a handle can be delivered as plastic waste.


Safety

See separate safety data sheet. Read the information on the packaging.
EU limit value for this product (cat. A/i): 140 g/l (2010). This product contains:
<80 g/l VOC.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt, Norway
Telephone: +47 712 91 700
E-mail: office@gjoco.no

