

FDV – Management, Operation and Maintenance

Proff Safe



Gjøco Proff Safe is a water-based, low-odor, and solvent-free PVA dispersion paint for indoor use in dry rooms. Gjøco Proff Safe is used as a primer on plaster, concrete, fiberglass wallpaper, environmentally friendly wallpaper, and fabric.

Revised

09.04.2026

| | | |
|---------------------------|-------------------------------------|---|
| Usage Instructions | Surface: | The surface must be clean and dry, with a minimum temperature of +5°C. |
| | Application Method: | Brush, roller, or spray. Spraying should be done by professionals. |
| | Thinner: | Water; thinning is usually not necessary. |
| | Storage: | Store and transport upright, in a dry and frost-free environment, and out of reach of children. |
| | Transport: | Not classified as hazardous goods under applicable regulations. |
| | Indoor Environment/Emissions | The product emits a mild vapor. |
| | Technical and Safety Data | A technical data sheet and safety data sheet (SDS / HSE data sheet) have been prepared for the product. See www.gjoco.no . VOC: EU limit value for this product (cat. A/g): 30 g/l (2010). The product contains <10 g/l VOC. |
| Maintenance | Cleaning: | For cleaning before repainting, it is recommended to use an alkaline cleaning agent such as Gjøco Interiørvask or Husvask. Follow the instructions on the product label. Newly painted surfaces should not be washed until after 3-4 weeks. Microfiber cloths with clean water or mild soapy water can be used. The washing water temperature should not exceed +40°C, and the pH should not exceed 9. Use of abrasive cleaning agents can damage the surface. Cleaning should be performed to avoid streaks and discoloration. Cleaning should be carried out as needed. The paint film will wear faster with frequent cleaning. |

Intervals:

The paint film is affected by mechanical wear and will degrade depending on the level of use. The maintenance interval will therefore vary based on actual wear.

Waste Management

Liquid paint should not be disposed of in sewage systems or nature, but should be delivered to an approved hazardous waste facility. Empty, clean, and dry plastic packaging without handles can be delivered as plastic waste.



Repairs/Damage

Repairs and damage should be remedied using the same type of product. Documentation must confirm that the same type of product was previously used if different products are considered. Repairs should be carried out to match the original treatment. For repainting or color changes, it is recommended to use the same product as before. Contact your dealer or a painting professional for assistance.

Eco-labeling

The product is approved by the Nordic Ecolabel (Svanen) and meets the requirements for the Svanen environmental label.



BREEAM-NOR v6.1:

- HEA02: The product complies with VOC content requirements in accordance with EU Directive 2004/42/EC and emission requirements tested in accordance with the ISO 16000 and ISO 11890 series.
- MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet.

Treated Surface/Type of Substrate:

Painted in Color:

Color Name:

NCS:

Batch Number:

Painting Performed By:

Date:

Signature:

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

Contact Information

Gjøco AS

Ørvegen 1160, 6639 Torvikbukt, Norway

Phone: +47 712 91 700

Email: office@gjoco.no

