

FDV – Management, Operation and Maintenance

Proff Safe



Gjøco Proff Safe is a water-based, low-odor, and solvent-free PVA dispersion paint for indoor use in dry rooms. Gjøco Proff Safe is used as a primer on plaster, concrete, fiberglass wallpaper, environmentally friendly wallpaper, and fabric.

Revised

27.02.2025

Usage Instructions	Surface:	The surface must be clean and dry, with a minimum temperature of +5°C.
	Application Method:	Brush, roller, or spray. Spraying should be done by professionals.
	Thinner:	Water; thinning is usually not necessary.
	Storage:	Store and transport upright, in a dry and frost-free environment, and out of reach of children.
	Transport:	Not classified as hazardous goods under applicable regulations.
	Indoor Environment/Emissions	The product emits a mild vapor.
Technical and Safety Data	A technical data sheet and safety data sheet (SDS / HSE data sheet) have been prepared for the product. See www.gjoco.no . VOC: EU limit value for this product (cat. A/g): 30 g/l (2010). The product contains <10 g/l VOC.	
Maintenance	Cleaning:	For cleaning before repainting, it is recommended to use an alkaline cleaning agent such as Gjøco Interiørvask or Husvask. Follow the instructions on the product label. Newly painted surfaces should not be washed until after 3-4 weeks. Microfiber cloths with clean water or mild soapy water can be used. The washing water temperature should not exceed +40°C, and the pH should not exceed 9. Use of abrasive cleaning agents can damage the surface. Cleaning should be performed to avoid streaks and discoloration. Cleaning should be carried out as needed. The paint film will wear faster with frequent cleaning.

Intervals:

The paint film is affected by mechanical wear and will degrade depending on the level of use. The maintenance interval will therefore vary based on actual wear.

Waste Management

Liquid paint should not be disposed of in sewage systems or nature, but should be delivered to an approved hazardous waste facility. Empty, clean, and dry plastic packaging without handles can be delivered as plastic waste.



Repairs/Damage

Repairs and damage should be remedied using the same type of product. Documentation must confirm that the same type of product was previously used if different products are considered. Repairs should be carried out to match the original treatment. For repainting or color changes, it is recommended to use the same product as before. Contact your dealer or a painting professional for assistance.

Environmental Labeling:

The product is approved by the Nordic Ecolabel (Svanen) and meets the requirements for the Svanen environmental label.



Treated Surface/Type of Substrate:

.....

Painted in Color:

Color Name:

.....

NCS:

.....

Batch Number:

.....

Painting Performed By:

.....

Date:

.....

Signature:

.....

The information in this data sheet is based on laboratory tests and practical experience. As our products are semi-finished goods, and usage conditions often fall outside our control, we only guarantee the product's quality. Products are delivered under our general terms of sale, delivery, and service unless otherwise agreed in writing. Minor product changes and data updates may occur without notice. This data sheet replaces previous editions and is automatically invalidated five years after its issue date.

Contact Information

Gjøco AS

Ørvegen 1160, 6639 Torvikbukta, Norway

Phone: +47 712 91 700

Email: office@gjoco.no

