

Product Data Sheet

Gjøco Proff Safe



Proff Safe is a fully matt waterborne primer/paint that is intended for painting walls and ceilings indoors. It has a high dry content, good covering capacity and provides an excellent carrying capacity with good adhesion on different substrates. Gjøco Proff Safe is used as a base paint and intermediate layer on building tiles of various types, plaster, concrete, fiberglass fabric, previously painted surfaces, etc.

Revised 18.03.2026

Symbols





Technical data

Type:	Pure PVA paint
Color:	White
Gloss:	Velvet 3
Specific gravity:	Approx. 1.4 kg/l
Solid content:	Approx. 42 volume%
Application method:	Roller, brush or airless spray.
Thinner/ cleaning agent:	Water
Recommended spreading rate:	8-10 m ² /liter
Guiding data for airless spray:	
Nozzle:	0.53 mm (0.021")
Spray angel:	65° - 80°
Pressure at nozzle:	Min. 150 kg/cm ²
Drying times (23 °C, 50 % R.H.):	Drying time deviates at changes in temperature, air humidity, air circulation and film thickness.
Dust dry:	1 hour
Interval between coats:	4 hours
Minimum application temperature:	+10 °C. Best results are obtained by application at room temperature.

Pretreatment

The surface must be clean and dry. Clean with Gjøco Husvask and rinse well with clean water. Smooth surfaces are dulled with sandpaper. Stained surfaces are primed with Gjøco Proff Isoler to prevent breakdown. Untreated masonry, previously limed and heavily contaminated substrates are scraped, brushed, and sewn with Gjøco Mineralprimer before applying Proff Safe.

Directions for use	Gjøco Safe is ready for use and must not be thinned. For best results apply once with Proff Safe and 1-2 times with selected finishing coat.
Storage	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
Eco-labeling	<p>Gjøco Proff Safe is approved by Ecolabelling Norway and meets the requirements for the Nordic Ecolabel.</p>  <p>BREEAM-NOR v6.1:</p> <ul style="list-style-type: none"> – HEA02: The product complies with VOC content requirements in accordance with EU Directive 2004/42/EC and emission requirements tested in accordance with the ISO 16000 and ISO 11890 series. – MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet.
Disposal of waste	<p>Liquid oil must not be emptied into sewers or into nature, but delivered to an environmental station. Empty, clean, and dry plastic packaging without a handle can be delivered as plastic waste.</p> 
Safety	<p>See separate safety data sheet. Read the information on the packaging. EU limit value for this product (cat. A/a): 30 g/l (2010). This product contains: <10 g/l VOC.</p>
Other information	<p>Application temperature in air and substrate must be at least +10°C. Stir well before use. Different production numbers are mixed before use. Package size: 9 liters</p>

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information **Gjøco AS**
 Ørvegen 1160, 6639 Torvikbukt, Norway
 Telephone: +47 712 91 700
 E-mail: office@gjoco.no

