

Product data sheet

Gjøco Proff Tapetlim



Gjøco Proff Tapetlim is a ready-to-use wallpaper glue for indoor use in dry rooms. It is recommended for hanging paper wallpapers but can also be used for slightly thicker wallpapers.

Revised 27.11.2024

Symbols



Technical Data

Type:	PVA dispersion
Color:	White
pH:	Approx. 7
Density:	Approx. 1,02 kg/l
Solids Content:	Approx. 11% by volume
Application Method	Brush, not a lint-shedding roller or wallpaper machine
Thinner / Cleaning Agent	Water. Wet glue and tools can be cleaned with soap and water. Dried glue can be removed with rubbing alcohol.
Recommended Coverage:	3 – 5 m ² per liter, depending on the substrate. Coarser surfaces and thicker wallpapers, such as fiberglass fabric, may require more glue.
Minimum Application Temperature	Minimum +18°C in the air and on the surface

Preparation

The surface must be clean, smooth, and dry. Old, loose paper wallpaper and old vinyl wallpaper should be completely removed. Loose fabric should be removed or smoothed over. Previously painted surfaces should be cleaned with Gjøco Interiørvask and rinsed thoroughly. Uneven surfaces should be filled and sanded. Highly absorbent substrates should be primed with Gjøco Tapetlim thinned with 1 part water.

Usage Instructions

Stir well before use. Apply the adhesive evenly to the backside of the wallpaper using a lint-free roller, brush, or wallpaper machine. Fold the wallpaper and let it rest for a few minutes before hanging. Follow the instructions from the wallpaper manufacturer.

Storage

Seal the lid tightly when storing the glue to prevent spills and drying out. Store and transport upright, frost-free, and preferably not below +10°C.

Waste Disposal

Liquid glue and wash water should not be poured into drains or released into nature. They should be delivered to an approved hazardous waste collection point. Empty, clean, and dry plastic packaging without handles can be disposed of as plastic waste.



Additional Information

Stir well before use. Wet glue and tools can be washed with soap and water. Dried glue can be removed mechanically or with rubbing alcohol. Packaging Sizes: 5 and 15 liters

Safety

Refer to the dedicated safety data sheet. Read the information on the packaging.

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and since the conditions under which they are used are often beyond our control, we can only guarantee the quality of the product itself. The products are supplied in accordance with our general terms of sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product modifications and to change the stated data without prior notice. This data sheet supersedes previous versions.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Phone number: +47 712 91 700
Email: office@gjoco.no

