

# Product data sheet

## Gjøco Proff Vegglim Extra



Gjøco Proff Vegglim Extra is a ready-mixed wallpaper paste for indoor use in dry rooms. It is easy to apply, has extra strong adhesion, and provides a long working time. It is used for hanging most types of wallpaper in dry rooms, such as textile wallpapers, fiberglass fabric, paintable wallpapers, vinyl wallpapers, and wallpapers with a non-woven backing.

Revised 27.11.2024

Symbols



### Technical Data

Type:	Ethyl vinyl acetate emulsion
Color:	White
pH:	Approx. 7
Density:	Approx. 1,02 kg/l
Solids Content:	Approx. 20% by volume
Application Method	Brush or roller
Thinner / Cleaning Agent	Water. Wet glue and tools can be cleaned with soap and water. Dried glue can be removed with rubbing alcohol.
Recommended Coverage:	3 – 5 m <sup>2</sup> per liter, depending on the substrate. Coarser surfaces and thicker wallpapers, such as fiberglass fabric, may require more glue.
Overpaintable:	Minimum 24 hours
Minimum Application Temperature	Minimum +18°C in the air and on the surface

### Preparation

The surface must be clean, smooth, and dry. If the substrate is made of particleboard or fiberboard, moisture should be checked before installation. Old, loose wallpaper and vinyl wallpaper must be completely removed. Previously painted surfaces should be cleaned with Gjøco Interiørvask and rinsed thoroughly. Glossy and semi-gloss surfaces should be dulled with sandpaper. Any cracks or uneven areas should be filled. Highly absorbent surfaces (e.g., masonry) should be primed with the adhesive thinned with 10-15% water.

### Usage Instructions

Apply the adhesive according to the wallpaper manufacturer's instructions. Press the wallpaper well against the surface to remove all air. Ensure there is enough adhesive under the seams. Fiberglass fabric should be applied immediately to the wet adhesive; otherwise, the installation time will be 10–30 minutes, depending on

---

air temperature and humidity. The adhesive contains water, which needs to be released, so allow a few minutes before applying the wallpaper.  
Working Temperature: Minimum +18°C for both the air and the surface.

---


**Storage**

Seal the lid tightly when storing the adhesive to prevent spills and drying out. Store and transport upright, frost-free, and preferably not below +10°C.

---

**Waste Disposal**

Liquid adhesive and wash water should not be poured into drains or released into nature. They should be delivered to an approved hazardous waste collection point. Empty, clean, and dry plastic packaging without handles can be disposed of as plastic waste.



**Additional Information**

Stir well before use. Wet glue and tools can be washed with soap and water. Dried glue can be removed mechanically or with rubbing alcohol.  
Packaging Sizes: 1, 5 and 15 liters

---

**Safety**

Refer to the dedicated safety data sheet. Read the information on the packaging.

---

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and since the conditions under which they are used are often beyond our control, we can only guarantee the quality of the product itself. The products are supplied in accordance with our general terms of sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product modifications and to change the stated data without prior notice. This data sheet supersedes previous versions.

---

**Contact Information**

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukt  
Phone number: +47 712 91 700  
Email: office@gjoco.no

