

FDV – Management, Operation and Maintenance

Proff Aquagrunn



Proff Aquagrunn is an impregnating and water-repellent wood primer for outdoor use on exterior cladding. It contains effective film-preserving agents to protect against surface mold. Proff Aquagrunn is white-pigmented. It is used on untreated and bare, paint-worn wood, as well as on pressure-treated wood.

Revised

10.04.2026

Usage Instructions	Surface:	The surface must be clean and dry.
	Application Method:	Brush. Should not be sprayed.
	Thinner:	Water, thinning is normally not necessary.
	Storage:	Store and transport upright, in a dry, frost-free place, and out of reach of children.
	Transport:	Not classified as dangerous goods according to current regulations.
	Indoor Environment/Emissions	This product is intended for outdoor use.
	Technical and Safety Data	A technical data sheet and a safety data sheet (SDS / HSE data sheet) have been prepared for the product. See www.gjoco.no . VOC: EU limit value for this product (cat. A/h): 30 g/l (2010). The product contains <30 g/l VOC.
Maintenance	Cleaning:	For annual cleaning, Gjøco Husvask is recommended. If the surfaces are contaminated with mildew, they can additionally be treated with Gjøco Sopp og algefjerner. For cleaning before repainting, Gjøco Kraftvask is recommended. Follow the instructions on the product.
	Intervals:	The impregnation will naturally break down due to weather exposure, varying based on local conditions and mechanical wear. Re-treatment should be done as needed, particularly when the surface film becomes dull and worn. Weather-exposed walls typically require more frequent maintenance than the rest of the building.
Waste Management	Liquid paint must not be poured into drains or released into nature, but should be delivered to an approved hazardous waste facility. Empty, clean, and dry plastic	

packaging without handles can be delivered as plastic waste..



Repairs/Damage

Repairs and damage should be fixed using the same type of product. Documentation is required if a different product is used, to confirm compatibility with previous treatments. Repairs should be carried out to match previous treatments. When repainting or changing colors, it is recommended to use the same product as before. Contact your dealer or painting contractor for advice.

Eco-labeling

BREEAM-NOR v6.1
– MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet.

Treated Surface/Type of Substrate:

.....

Painted in Color:

Color Name:

.....

NCS:

.....

Batch Number:

.....

Painting Performed By:

.....

Date:

.....

Signature:

.....

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

Contact Information

Gjøco AS

Ørvegen 1160, 6639 Torvikbukt, Norway

Phone: +47 712 91 700

Email: office@gjoco.no

