

# FDV – Management, Operation and Maintenance

## Proff Aquagrunn



Proff Aquagrunn is an impregnating and water-repellent wood primer for outdoor use on exterior cladding. It contains effective film-preserving agents to protect against surface mold. Proff Aquagrunn is white-pigmented. It is used on untreated and bare, paint-worn wood, as well as on pressure-treated wood.

Revised

27.02.2025

<b>Usage Instructions</b>	<b>Surface:</b>	The surface must be clean and dry.
	<b>Application Method:</b>	Brush. Should not be sprayed.
	<b>Thinner:</b>	Water, thinning is normally not necessary.
	<b>Storage:</b>	Store and transport upright, in a dry, frost-free place, and out of reach of children.
	<b>Transport:</b>	Not classified as dangerous goods according to current regulations.
	<b>Indoor Environment/Emissions</b>	This product is intended for outdoor use.
<b>Technical and Safety Data</b>	A technical data sheet and a safety data sheet (SDS / HSE data sheet) have been prepared for the product. See <a href="http://www.gjoco.no">www.gjoco.no</a> . VOC: EU limit value for this product (cat. A/h): 30 g/l (2010). The product contains <30 g/l VOC.	
<b>Maintenance</b>	<b>Cleaning:</b>	For annual cleaning, Gjøco Husvask is recommended. If the surfaces are contaminated with mildew, they can additionally be treated with Gjøco Sopp og algefjerner. For cleaning before repainting, Gjøco Kraftvask is recommended. Follow the instructions on the product.
	<b>Intervals:</b>	The impregnation will naturally break down due to weather exposure, varying based on local conditions and mechanical wear. Re-treatment should be done as needed, particularly when the surface film becomes dull and worn. Weather-exposed walls typically require more frequent maintenance than the rest of the building.
<b>Waste Management</b>	Liquid paint must not be poured into drains or released into nature, but should be delivered to an approved hazardous waste facility. Empty, clean, and dry plastic	

---

packaging without handles can be delivered as plastic waste..



---

**Repairs/Damage**

Repairs and damage should be fixed using the same type of product. Documentation is required if a different product is used, to confirm compatibility with previous treatments. Repairs should be carried out to match previous treatments. When repainting or changing colors, it is recommended to use the same product as before. Contact your dealer or painting contractor for advice.

---

**Treated Surface/Type of Substrate:**

.....

**Painted in Color:**

**Color Name:**

.....

**NCS:**

.....

**Batch Number:**

.....

**Painting Performed By:**

.....

**Date:**

.....

**Signature:**

.....

---

The information in this data sheet is based on laboratory tests and practical experience. As our products are semi-finished goods, and usage conditions often fall outside our control, we only guarantee the product's quality. Products are delivered under our general terms of sale, delivery, and service unless otherwise agreed in writing. Minor product changes and data updates may occur without notice. This data sheet replaces previous editions and is automatically invalidated five years after its issue date.

---

**Contact Information**

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukt, Norway  
Phone: +47 712 91 700  
Email: office@gjoco.no

