

Product datasheet

Proff Aquagrunn



Proff Aquagrunn is an impregnating and water-repellent wood primer for outdoor use on exterior panels of houses. Contains effective film preservatives against surface fungi. Used on untreated and bare paint-worn wood, and on impregnated wood.

Revised 11.12.2024

Symbols



Technical data


Type:	Primer based on alkyd oils
Color:	White pigmented and clear
Specific gravity:	Approx. 1.02 kg/l
Solid content:	Approx. 22 volum%
Application method:	Brush. Do not spray.
Thinner / cleaning agent:	Water
Recommended spreading rate:	
Planed wood:	6-8 m ² /liter
Unplaned wood:	4-7 m ² /liter
Drying time (23 °C, 50 % R.H.):	Depends on temperature, humidity, wind and film thickness.
Dust dry:	2 hours
Interval between coats, minimum:	12 hours

Pretreatment

The substrate must be firm, clean and dry. New wood that has been untreated for more than 4 weeks must be wire brushed to remove loose wood fibers. Vacuum impregnated windows, etc. must be degreased before priming. Smooth and hard surfaces such as planed wood should be wire brushed before priming, and sharp edges rounded. Previously painted wood should be scraped clean of loose paint and weathered surfaces should be wire brushed down to fresh wood. Grease and other contaminants are removed with Gjøco Kraftvask.

Directions for use

Apply 1 coat of Proff Aquagrunn. Proff Aquagrunn should not form a film – spread evenly. Wipe away any excess primer. Treat all end timbers/cut surfaces wet-on-wet 3–4 times. Further treatment should be carried out as soon as possible and within 1 month.

Storage	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
Disposal of waste	Liquid stain should not be emptied into sewers or into nature, but delivered to an environmental waste disposal station. Empty, clean and dry plastic packaging without a handle can be delivered as plastic waste. 
Other information	The product is ready to use and should not be thinned. Stir well before and during use. Further treatment with other products must take place within 1 month. Proff Aquagrunn white pigmented will affect the color of the top coat when used under transparent stains. Under transparent stains, a clear primer is recommended. For more detailed information, see the safety and technical data sheet. Packaging size: 9 liters.
Safety	See separate safety data sheet. Read the information on the packaging. EU limit value for this product (kat. A/h): 30 g/l (2010). This product contains: <20 g/l VOC.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information **Gjøco AS**
Ørvegen 1160, 6639 Torvikbukt
Telephone: +47 712 91 700
E-mail: office@gjoco.no

