

# Product Data Sheet

## Proff Aquagrunn



Proff Aquagrunn is an impregnating and water-repellent wood primer for outdoor use on exterior panels of houses. Contains effective film preservatives against surface fungi. Used on untreated and bare paint-worn wood, and on impregnated wood.

Revised 18.03.2026

Symbols



### Technical data


Type:	Primer based on alkyd oils
Color:	White pigmented and clear
Specific gravity:	Approx. 1.02 kg/l
Solid content:	Approx. 22 volum%
Application method:	Brush. Do not spray.
Thinner / cleaning agent:	Water
Recommended spreading rate:	
Planed wood:	6-8 m <sup>2</sup> /liter
Unplaned wood:	4-7 m <sup>2</sup> /liter
Drying time (23 °C, 50 % R.H.):	Depends on temperature, humidity, wind and film thickness.
Dust dry:	2 hours
Interval between coats, minimum:	12 hours

### Pretreatment

The substrate must be firm, clean and dry. New wood that has been untreated for more than 4 weeks must be wire brushed to remove loose wood fibers. Vacuum impregnated windows, etc. must be degreased before priming. Smooth and hard surfaces such as planed wood should be wire brushed before priming, and sharp edges rounded. Previously painted wood should be scraped clean of loose paint and weathered surfaces should be wire brushed down to fresh wood. Grease and other contaminants are removed with Gjøco Kraftvask.

### Directions for use

Apply 1 coat of Proff Aquagrunn. Proff Aquagrunn should not form a film – spread evenly. Wipe away any excess primer. Treat all end timbers/cut surfaces wet-on-wet 3–4 times. Further treatment should be carried out as soon as possible and within 1 month.

<b>Storage</b>	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
<b>Eco-labeling</b>	BREEAM-NOR v6.1 – MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet.
<b>Disposal of waste</b>	Liquid stain should not be emptied into sewers or into nature, but delivered to an environmental waste disposal station. Empty, clean and dry plastic packaging without a handle can be delivered as plastic waste. 
<b>Other information</b>	The product is ready to use and should not be thinned. Stir well before and during use. Further treatment with other products must take place within 1 month. Proff Aquagrunn white pigmented will affect the color of the top coat when used under transparent stains. Under transparent stains, a clear primer is recommended. For more detailed information, see the safety and technical data sheet. Packaging size: 9 liters.
<b>Safety</b>	See separate safety data sheet. Read the information on the packaging. EU limit value for this product (kat. A/h): 30 g/l (2010). This product contains: <20 g/l VOC.

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

**Contact information**      **Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukt  
Telephone: +47 712 91 700  
E-mail: office@gjoco.no

