



FDV - Management, Operation and Maintenance

GjøcoUrea P 400



GjøcoUrea P 400 is a two-component, solvent-free pure polyurea. The product is applied using a two-component high-pressure spray and forms a waterproof and protective coating for use on bridges, roofs, the fish processing industry, and water facilities in general.

Revised	14.10.2025	
Application Instructions	Substrate:	The substrate must be solid, clean, dry, and free of grease.
	Application method:	Two-component high-pressure spray.
	Thinner:	The product must not be thinned.
	Storage:	The product must be stored in accordance with national regulations. The packaging must be kept tightly closed and stored in a dry place at a stable temperature. The product must be transported and stored upright, dry, and frost-free.
	Indoor environment / emissions:	The product has low emissions.
Product Data Sheet and Safety Data Sheet	A product data sheet and safety data sheet (SDS) have been prepared for the product. See www.gjoco.no .	
Maintenance	Cleaning:	For cleaning, Gjøco Gulv og Panelrens or another suitable cleaning agent is recommended. Follow the instructions on the product. See the product data sheet for additional information.
	Interval:	The coating is affected by mechanical stress and wears depending on use. Maintenance intervals will therefore vary according to need. For maintenance of polyurea, please contact us
Waste Management	Uncured product must not be poured into drains or released into the environment, but should be delivered to an approved waste collection facility.	
		

Repairs / Damage

For repairs and damage, contact us for more information. When repairing damage, the work should be carried out so that it does not differ from previous treatments.

Treated Surface / Type of Substrate:**Painted in Color:****Color Name:****NCS:****Batch Number:****Painting Work Performed By:****Date:****Signature:**

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished, and since the conditions under which they are used are often beyond our control, we can only guarantee the quality of the product itself. The products are supplied in accordance with our general terms of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to make minor product modifications and to change the specified data without prior notice. This data sheet replaces previous editions and is automatically void five years after the date of issue.

Contact Information

Gjøco AS, Galterud
Sagmoen 100, NO-2223 Galterud, Norway
Phone: +47 712 91 700
Email: office@gjoco.no

