



FDV - Management, Operation and Maintenance

GjøcoPoxy L



GjøcoPoxy L is a solvent-free, two-component epoxy adhesive for concrete. It is designed for bonding fresh concrete to existing concrete, concrete to concrete, and concrete to steel.

GjøcoPoxy L provides a monolithic, load-transferring bond between new and existing concrete.

Revised

28.10.2025

Application Instructions	Substrate:	The surface must be solid, clean, dry, and free from grease. The temperature of both substrate and air must be at least +5 °C and at least 3 °C above the current dew point.
	Application method:	Paint roller, brush, or spatula.
	Storage:	The product must be stored in accordance with national regulations. Containers should be tightly sealed and kept dry at a stable temperature. The product must be transported and stored upright, in a dry and frost-free environment.
	Indoor environment / emissions:	The product has low emissions.
Product Data Sheet and Safety Data Sheet	A product data sheet and safety data sheet (SDS) have been prepared for the product. See www.gjoco.no .	
Maintenance	Cleaning:	Before repainting, Gjøco Gulv- og panelrens or another suitable cleaning agent is recommended.
	Interval:	The coating is affected by mechanical stress and wears depending on the level of use. Maintenance intervals will therefore vary according to need.
Waste Management	Liquid epoxy must not be poured into drains or released into the environment but should be delivered to a recycling station. Uncured epoxy can be delivered to recycling stations as residual waste; however, it is recommended to contact the specific station for guidance, as local regulations may vary.	



Repairs / Damage

Repairs and damage should be remedied using the same type of product. If other products are used, it must be documented that they are of the same type as previously applied. When repairing damage, the work should be carried out so that it does not differ from previous treatments. For repainting or color changes, it is recommended to use the same product as before. Contact the supplier or painting company.

Treated Surface / Type of Substrate:

Painted in Color:**Color Name:**

NCS:

Batch Number:

Painting Work Performed By:

Date:

Signature:

The information in this data sheet is based on laboratory tests and practical experience. Since the conditions under which the products are used are often beyond our control, we can only guarantee the quality of the product itself. The products are supplied in accordance with our general terms of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint should be considered a semi-finished product, and the result depends on surface preparation, temperature, application, type of substrate, etc. This data sheet supersedes all previous editions.

Contact Information

Gjøco AS, Galterud
Sagmoen 100, NO-2223 Galterud, Norway
Phone: +47 712 91 700
Email: office@gjoco.no

