



## FDV – Management, operation, and maintenance

### Herregård Oljebeis Matt



Herregård Oljebeis Matt is a weather-resistant, alkyd-modified stain for outdoor use. It is used on new wood, timber, pressure-treated wood, and previously stained wood. Herregård Oljebeis Matt provides a matte and sophisticated appearance. Contains effective film-preserving agents against mildew.

Revised

10.04.2026

#### Application Instructions

##### Substrate:

The surface must be dry and free of frost, with a minimum temperature of +5 °C.

##### Application Methods:

Apply with a brush, roller, or spray. Spraying should be done by professionals.

##### Thinner:

Water; thinning is normally not necessary.

##### Storage:

Store and transport upright, dry, and frost-free, and keep out of reach of children.

##### Transport:

Not classified as dangerous goods under current regulations.

##### Indoor Environment/Emission:

The product is intended for outdoor use.

#### Technical and Safety Data

A technical data sheet and safety data sheet (SDS) have been prepared for the product. See [www.gjoco.no](http://www.gjoco.no). VOC: EU limit value for this product (cat. A/e): 130 g/l (2010). The product contains <100 g/l VOC.

#### Maintenance

##### Cleaning:

For annual cleaning, Gjøco Husvask is recommended. For cleaning prior to repainting, Gjøco Kraftvask is recommended. Follow the instructions on the product. Newly painted wood should not be washed until after 3–4 weeks.

##### Interval:

The paint film naturally breaks down due to weather exposure and will vary depending on local conditions. Repainting should therefore be done as needed, when the film appears dull and worn. Weather-exposed walls are more susceptible to the elements and typically require more frequent repainting than the rest of the building.

**Waste Disposal**

Liquid paint must not be poured into drains or released into the environment, but must be delivered to an approved hazardous waste facility. Empty, clean, and dry plastic containers without handles can be disposed of as plastic waste. Empty metal cans must be delivered to a recycling station.



**Repairs/Damage**

Repairs and damage should be touched up using the same type of product. Documentation must show that the same type of product was previously used if other products are applied. Repairs should be carried out in such a way that they do not deviate from previous treatments. When repainting or changing color, it is recommended to use the same product that was used before. Contact your dealer or paint supplier for further advice.

**Eco-labeling**

BREEAM-NOR v6.1  
– MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet.

**Surface/Material Information**

Painted in color:

Color name:

NCS:

Batch number:

Work performed by:

Date:

Signature:

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

**Contact Information**

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukt, Norway  
Phone: +47 712 91 700  
Email: office@gjoco.no

