



## FDV – Management, operation, and maintenance

### Gjøco Primer for mur og betong



Gjøco Primer for mur og betong is suitable for use on untreated masonry, concrete, brick, plaster, and concrete roof tiles before repainting with a suitable topcoat. Brick must be plastered before repainting. The primer is also well-suited as a dust binder and impregnation for garage floors, walls, etc., where painting is not desired. It is recommended as a primer for roof tiles before repainting with Gjøco Takdekk. The primer seals the pores in the roof tiles, preventing frost damage and peeling.

Revised

15.01.2025

#### Application Instructions

**Substrate:**

The surface must be clean and dry, with a minimum temperature of +5 °C.

**Application Methods:**

Coarse brush, roller, or spray

**Thinner:**

Water, thinning is usually not necessary.

**Storage:**

Store and transport upright, dry, and frost-free, out of reach of children.

**Transport:**

Not classified as dangerous goods under applicable regulations.

**Indoor Environment/Emission:**

The product is intended for outdoor use.

#### Technical and Safety Data

A technical data sheet and safety data sheet (SDS/HMS) have been prepared for the product. See [www.gjoco.no](http://www.gjoco.no). VOC: EU limit for the product (category A/e): 130 g/l (2010). The product contains <30 g/l VOC.

#### Maintenance

**Cleaning:**

For annual cleaning, Gjøco Husvask is recommended. If other cleaning agents are used, the pH value should not exceed pH 9. If surfaces are contaminated with black mold, they can additionally be treated with Gjøco Sopp- og grønskefjerner. For cleaning before repainting, Gjøco Kraftvask is recommended. Follow the instructions on the product.

**Interval:**

The paint film naturally breaks down due to weather exposure and will vary based on local conditions. Repainting must therefore be done as needed, when the film appears dull and worn. The weather wall(s) are more exposed to the weather and typically require more frequent repainting than the rest of the building.

**Waste Disposal**

Liquid paint should not be disposed of in sewer drains or in nature, but should be delivered to an approved hazardous waste facility. Empty and dry packaging should be delivered to an approved facility. For further information, refer to the regulations for hazardous waste.

**Repairs/Damage**

Repairs and damages should be addressed with the same type of product. Documentation must be provided to confirm it is the same type previously used if other products are employed. Repairs should be carried out to match previous treatments. For repainting or color changes, it is recommended to use the same product as before. Contact the dealer or paint company for advice.

**Surface/Material Information****Painted in color:****Color name:****NCS:****Batch number:****Work performed by:****Date:****Signature:**

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

**Contact Information**

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukt  
Phone: +47 712 91 700  
Email: office@gjoco.no

