

Product datasheet

Gjøco Primer for mur og betong



Gjøco Primer for masonry and concrete is suitable for use on untreated masonry, concrete, brick, plaster and concrete roof tiles before painting with a suitable top coat. Bricks must be plastered before painting. The primer is also well suited as a dust binder and impregnation on garage floors, walls, etc. where paint is not desired. Recommended as a primer for roof tiles before painting with Gjøco Takdekk. The primer seals the pores in the roof tiles, and prevents frost cracking and flaking.

Revised 08.10.2025

Symbols




Technical data

Type:	Water-thinnable unpigmented impregnation based on acrylic.
Color:	Colorless when dry, whitish when wet.
Specific gravity:	Approx. 1 kg/l
Application method:	Coarse brush, roller or spray.
Thinner / cleaning agent:	Water
Recommended spreading rate:	5-7 m ² /liter, depending on the substrate.
Recommended data for airless spray:	
Nozzle tip:	0.46 mm (0.018")
Spray angle degrees:	65°–80°
Pressure at nozzle:	15–18 MPa (150–180 kg/cm ²)
	The choice of nozzle, fan angle, and pressure must be adjusted to the specific spray equipment and substrate.
Drying time (23 °C, 50 % R.H.):	
Dust dry:	1 hours
Interval between coats:	4 hours
Minimum application temperature:	+5 °C

Pretreatment

Loose masonry and plaster should be brushed/scraped. On new concrete/walls that are to be painted after priming with Gjøco Primer for masonry and concrete, the cement film must be removed by mechanical grinding. Cement and concrete roof tiles should be cleaned with Gjøco Husvask and a high-pressure washer. It is important that loose particles, algae, fungus, moss and other contamination are removed. The substrate must be dry before Gjøco Primer for masonry and concrete is applied. When using on concrete and cement elements, any moisture and release coating must be checked.

Directions for use	Gjøco Primer for masonry and concrete is ready to use and should not normally be thinned. Apply 1-2 coats depending on the nature and absorbency of the substrate. The primer should absorb into the substrate and not form a film. Apply with a roller, brush or spray.
Storage	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.
Disposal of waste	Liquid paint must not be emptied into sewers or into nature, but must be delivered to an approved hazardous waste collection point. Empty, clean and dry plastic packaging without handling, can be delivered as plastic waste. 
Other information	Stir well before use. Package sizes: 0.75 and 10 liters.
Safety	See separate safety data sheet. Read the information on the packaging. EU limit value for this product (kat. A/d): 130 g/l (2010). This product contains: <30 g/l VOC.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information **Gjøco AS**
 Ørvegen 1160, 6639 Torvikbukt
 Telephone: +47 712 91 700
 E-mail: office@gjoco.no

