## Product datasheet Gjøco AquaStop C





Gjøco AquaStop C is a water-thinnable impregnation based on nanotechnology that provides a water-repellent surface on mineral substrates such as masonry, plaster, concrete and stone both indoors and outdoors. Provides extra protection against black mold, algae, moisture and frost cracking.

Gjøco AquaStop C is applied directly to substrates such as paving stones, plastered leca, plastered foundations, free-standing walls, bricks, concrete/brick stairs, ceramic tiles, roof tiles and joints.

Revised

04.12.2024

Symbols



Technical data	Туре:	Water-thinnable unpigmented impregnation	
	Color:	Colorless when dry, whitish when wet.	
	Specific gravity:	Ca. 1 kg/l	
	Application method:	Coarse brush, roller, or spray.	
	Thinner / cleaning agent:	Water	
	Recommended spreading rate:	8-10 m²/litre, depending on the substrate.	
	Drying time (23 °C, 50 % R.H.):		
	Dust dry:	Ca. 24 hour	
	Minimum application temperature:	+5 °C. Low temperatures result in longer drying time.	
Pretreatment		Loose masonry and plaster should be brushed/scraped. The substrate must be clean and dry before using AquaStop C.	
Directions for use	skal være over 5 °C. Anbef i original uåpnet emballasje Påføres med rull, grov pen behandlingen innen 3 time	Fortynning av produktet er ikke nødvendig. Påføringstemperatur i luft og underlag skal være over 5 °C. Anbefales ikke til bruk på ikke-sugende underlag. Kan lagres i original uåpnet emballasje opp til 24 måneder etter produksjonsdato. Påføres med rull, grov pensel eller sprøyte. På svært sugende underlag gjentas behandlingen innen 3 timer. Kan tilsettes i fugemasser og betong hvor 1/3 av vannet erstattes med AquaStop C. Det anbefales å teste et mindre areal før påføringen utføres.	
Storage	Seal the lid tightly when storing paint to prevent spillage and drying. The paint must be transported and stored upright, dry and frost-free.		

Disposal of waste	The product should not be emptied into sewers or into the environment, but delivered to an approved hazardous waste collection point. Empty, clean and dry packaging should be delivered to an approved collection point.	
Other information		
Safety	See separate safety data sheet. Read the information on the packaging.	

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information

**Gjøco AS** Ørvegen 1160, 6639 Torvikbukt Telephone: +47 712 91 700 E-mail: office@gjoco.no

