



FDV - Management, Operation and Maintenance

GjøcoPoxy C



GjøcoPoxy C is a 2-component, solvent-free epoxy coating for floors and walls in industrial and commercial buildings. It is intended for use on concrete, cement-based substrates, steel, aluminum, and similar materials. It is recommended to apply the epoxy primer, GjøcoPoxy BP, directly on cement-based substrates to ensure good adhesion before applying GjøcoPoxy C.

Revised

14.10.2025

Application Instructions

Substrate:

The substrate must be solid, clean, dry, free of dust and grease, and have a temperature of at least +12 °C for both substrate and air, and at least 3 °C above the current dew point.

Application method:

Roller, mop, rubber squeegee, or brush.

Thinner:

The product must not be thinned.

Storage:

Store in a dry, frost-free place.

Indoor environment / emissions:

The product has low emissions.

Product Data Sheet and Safety Data Sheet

A product data sheet and safety data sheet (SDS) have been prepared for the product. See www.gjoco.no.

Maintenance

Cleaning:

Before repainting, Gjøco Gulv og Panelrens is recommended. Follow the instructions on the product. See the Product Data Sheet for more information.

Interval:

The coating is affected by mechanical stress and wears depending on the level of use. Maintenance intervals will therefore vary according to need.

Waste Management

Liquid epoxy must not be poured into drains or released into the environment but should be delivered to a recycling or waste collection station. Cured epoxy can be disposed of at waste collection stations as residual waste, but it is recommended to contact the local facility for specific guidance, as regulations may vary locally.



Repairs / Damage

Repairs and damage should be remedied using the same type of product. If other products are used, it must be documented that they are of the same type as previously applied. When repairing damage, the work should be carried out so that it does not differ from previous treatments. For repainting or color changes, it is recommended to use the same product as before. Contact the supplier or painting company.

Treated Surface / Type of Substrate:**Painted in Color:****Color Name:****NCS:****Batch Number:****Painting Work Performed By:****Date:****Signature:**

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished, and since the conditions under which they are used are often beyond our control, we can only guarantee the quality of the product itself. The products are supplied in accordance with our general terms of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to make minor product modifications and to change the specified data without prior notice. This data sheet replaces previous editions and is automatically void five years after the date of issue.

Contact Information

Gjøco AS, Galterud
Sagmoen 100, NO-2223 Galterud, Norway
Phone: +47 712 91 700
Email: office@gjoco.no

