



FDV – Management, operation, and maintenance Herregård Exclusive Oljebeis



Herregård Exclusive Oljebeis is a thixotropic alkyd oil-based stain with added film protection against mildew. It penetrates well into the wood, providing effective impregnation while forming a weather-resistant film. Herregård Exclusive Oljebeis is used on new or previously stained wood surfaces. It can also be used on pressure-treated materials. No primer is required.

Revised

10.04.2026

Application Instructions

Substrate:

The surface must be dry and free of frost, with a minimum temperature of -5 °C.

Application Methods:

Brush, roller, or spray. Spraying should be carried out by professionals.

Thinner:

White Spirit, thinning is normally not necessary.

Storage:

Store and transport upright, dry, and frost-free, out of reach of children.

Transport:

Not classified as dangerous goods under applicable regulations.

Indoor Environment/Emission:

The product is intended for outdoor use.

Technical and Safety Data

A technical data sheet and safety data sheet (SDS / HSE data sheet) have been prepared for this product. See www.gjoco.no. VOC: EU limit value for this product (cat. A/e): 400 g/l (2010). The product contains <400 g/l VOC.

Maintenance

Cleaning:

For annual cleaning, Gjøco Husvask is recommended. For cleaning before repainting, Gjøco Kraftvask is recommended. Follow the instructions on the product label. Newly painted wood should not be washed for 3-4 weeks.

Interval:

The paint film naturally breaks down due to weather exposure, and this will vary depending on local conditions. Repainting should be done as needed, particularly when the film becomes dull and worn. Weather-exposed walls typically require more frequent repainting than the rest of the building.

Waste Disposal

Liquid paint should not be disposed of in sewage drains or the environment but should be delivered to an approved hazardous waste collection facility. Empty, clean, and dry plastic containers without handles can be disposed of as plastic waste.



Repairs/Damage

Repairs and damage should be touched up using the same type of product. Documentation must show that the same type of product was previously used if other products are applied. Repairs should be carried out in such a way that they do not deviate from previous treatments. When repainting or changing color, it is recommended to use the same product that was used before. Contact your dealer or paint supplier for further advice.

Eco-labeling

BREEAM-NOR v6.1
– MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet.

Surface/Material Information

Painted in color:

Color name:

NCS:

Batch number:

Work performed by:

Date:

Signature:

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbuk
Phone: +47 712 91 700
Email: office@gjoco.no

