

Product Data Sheet

Gjøco Proff Sprøytesparkel Joint



Gjøco Proff Sprøytesparkel Joint is a ready-mixed sprayable joint filler designed for joints and corners with an adhesive effect. It is specially formulated for joint filling with paper tape and corner reinforcement on gypsum boards and concrete surfaces indoors.

Revised 05.12.2024

Symbols



Technical Data

Type:	Latex polymer
Color:	Light gray
Filler:	Light filler and white dolomite
Density:	Approx. 1.2 kg/l
pH:	Approx. 9
Grain Size:	Max 0,15 mm
Application Method:	Spray
Thinner/Cleaning Agent:	Water. Should normally not be thinned.
Consumption	Approx. 0.3 liters/m ² for joint filling on gypsum boards.
Drying Time:	Depends on substrate, layer thickness, temperature, and humidity
Minimum Application Temperature:	+5°C
Shelf Life:	1 year in unopened packaging
Flammability:	Does not spread or support combustion

Surface Preparation

The surface must be clean, dry, grease-free, and free from loose particles.

Application

Apply using a spray. After the surface dries, sand it using sandpaper with a grit size of 120-150. Eye and respiratory protection are recommended during sanding. Wipe off dust before the next treatment. Sanded surfaces should be primed before wallpapering.

Environmental Labeling

Gjøco Proff Sprøytesparkel Joint is approved by Miljømerking Norge and meets the requirements for the Swan eco-label.



The product has been tested according to BREEAM-NOR (2016) criteria and satisfies BREEAM-NOR HEA 02.

Contains no substances from the A20 list.

Storage

This product is a date-marked perishable item. Unopened packaging can be stored in a cool, dark, and frost-free place for up to 12 months. Once opened, close the container tightly. Should be stored and transported standing, dry, and frost-free.

Waste Disposal

Do not dispose of the product or wash water in sewers or nature. Instead, deliver to an approved facility for hazardous waste. Empty, clean, and dry plastic containers without handles can be recycled as plastic waste.



Additional Information

Store in a dry, frost-free place, protected from sunlight. Unopened packaging can be stored for up to 12 months. Check the consistency and smell before use if stored longer. Available in 15 L bucket and 15 L bag.

Safety

Refer to the safety data sheet for detailed safety information. Follow all instructions on the packaging. Use eye protection when sanding larger surfaces.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and since conditions of use are often beyond our control, we can only guarantee the product's quality. Products are supplied according to our general terms of sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and update the stated data without prior notice. This data sheet supersedes earlier versions.

Contact Information

Gjøco AS
 Ørvegen 1160, 6639 Torvikbukt
 Phone: +47 712 91 700
 Email: office@gjoco.no

