



## FDV – Management, Operation, and Maintenance

### Gjøco Proff Sprøytesparkel Medium



Gjøco Proff Sprøytesparkel Medium is a ready-mixed, grey all-purpose filler. It has good filling capacity and a smooth consistency, making it easy to work with. Suitable for resurfacing, joint filling, and full-surface filling. Compatible with most substrates in both new construction and renovation projects. Suitable for embedding paper tape. Gjøco Proff Sprøytesparkel Medium in 15-liter buckets can also be used as a roller-applied filler.

Revised: 11.06.2025

#### Instructions for Use

<b>Substrate:</b>	The surface must be clean and dry.
<b>Type:</b>	Latex polymer with lightweight filler and white dolomite.
<b>Application method:</b>	Spray.
<b>Cleaning agent:</b>	Water.
<b>Thinner:</b>	Normally should not be thinned.
<b>Storage:</b>	Store in a dry and frost-free place, out of reach of children.
<b>Transport:</b>	Not classified as hazardous goods according to current regulations.

#### Technical Data and Safety Information

A technical data sheet and a safety data sheet (HMS / SDS) have been prepared for the product. See [www.gjoco.no](http://www.gjoco.no).

Gjøco Proff Sprøytesparkel Medium is Nordic Swan Ecolabel certified.



#### Maintenance

<b>Cleaning:</b>	Not applicable. The product is not used on its own.
<b>Interval:</b>	Not applicable. The product is not used on its own.

#### Waste Disposal

The product must be delivered to an approved facility for such waste. The product must not be poured into the environment, sewage, or water. Empty and dry packaging should be delivered to an approved facility.



#### Repairs / Damage

Repairs and damage should be repaired using the same type of product. If other products are used, it must be documented that they are of the same type as previously used. When repairing damage, the work should be carried out so that it does not differ from previous treatments. When repainting or changing color, it is

---

recommended to use the same product as before. Contact your dealer or paint company for advice.

---

**Treated Surface / Type of Substrate:**

**Batch Number:**

**Painting Work Performed By:**

**Date:**

**Signature:**

---

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and since the conditions under which the products are used are often beyond our control, we can only guarantee the quality of the product itself. The products are supplied in accordance with our general terms and conditions for sales, delivery, and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to amend the specified data without prior notice. This data sheet replaces previous versions and is automatically void five years after the publication date.

---

**Contact Information**

**Gjøco AS**

Ørvegen 1160, 6639 Torvikbukt, Norway

Phone: +47 712 91 700

Email: [office@gjoco.no](mailto:office@gjoco.no)

