

## Product Data Sheet

## Gjøco Proff Sprøytesparkel Medium



Gjøco Proff Sprøytesparkel Medium is a ready-mixed, grey all-purpose filler. It has good filling capacity and a smooth consistency, making it easy to work with. It is suitable for patching, joint filling, and overall smoothing. It works well on most substrates in both new construction and renovation projects. It is also suitable for embedding paper tape. Gjøco Proff Sprøytesparkel Medium in a 15-liter bucket can also be used as a roller filler.

Revised 05.12.2024

Symbols



### Technical Data

Type:	Latex polymer
Color:	Gray
Filler:	Light filler and white dolomite
pH:	Approx. 9
Grain Size:	Max 0,2 mm
Application Method:	Spray
Thinner/Cleaning Agent:	Water. Normally, it should not be thinned.
Consumption	Approx. 0.3 liters/m <sup>2</sup> for joint filling on drywall. Full smoothing with 1 mm layer thickness: Approx. 1 liter/m <sup>2</sup> .
Drying Time:	Depends on substrate, layer thickness, temperature, and humidity
Minimum Application Temperature:	+5°C
Shelf Life:	1 year in unopened packaging

### Surface Preparation

The surface must be clean, dry, grease-free, and free from loose particles. Glossy and contaminated surfaces should be cleaned with Gjøco Interiørvask.

### Application

Apply with a spray. It can also be rolled. The surface temperature must be at least +5°C. Once the surface is dry, sand it with sandpaper of grain size 150–180. Eye and respiratory protection is recommended when sanding. Wipe off dust before the next application. Surfaces that have been smoothed should be primed before wallpapering.

### Environmental Labeling

Gjøco Proff Sprøytesparkel Medium is approved by the Norwegian Environmental Certification and meets the criteria for the Swan eco-label. The product has been tested according to the test requirements set by BREEAM-NOR (2016) and complies with BREEAM-NOR HEA 02.

Gjøco Proff Sprøytesparkel Medium does not contain any substances on the A20 list.



#### Storage

The putty is a perishable product marked with an expiration date. Unopened packaging can be stored in a cool, dark, and frost-free place for up to 12 months. Opened containers should be tightly sealed. The putty should be transported and stored standing, in a dry and frost-free environment.

#### Waste Disposal

Putty and wash water should not be discharged into sewage systems or nature but should be delivered to an approved hazardous waste collection facility. Empty, clean, and dry plastic packaging without handles can be disposed of as plastic waste.



#### Additional Information

Store in a dry, frost-free location and shielded from sunlight. Unopened packaging can be stored for 12 months. It may also remain usable after 12 months, but check consistency and smell. Packaging sizes: 15 L pail and 15 L bag.

#### Safety

Refer to the safety data sheet for detailed safety information. Follow all instructions on the packaging. Use eye protection when sanding larger surfaces.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and since conditions of use are often beyond our control, we can only guarantee the product's quality. Products are supplied according to our general terms of sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and update the stated data without prior notice. This data sheet supersedes earlier versions.

#### Contact Information

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukt  
Phone: +47 712 91 700  
Email: office@gjoco.no

