

Product datasheet

Våtrom 05



Gjøco Våtrom 05 is a moisture-resistant wall and ceiling paint for indoor use in wet rooms such as bathrooms, laundry rooms, kitchens, and garages. It provides a washable and durable surface that does not yellow. Suitable for walls made of, for example, paintable wallpaper, building boards, MDF, fiberglass fabric, woven fabric, wallpaper, plaster, masonry, concrete, and sand filler. It can also be used on paneling. Should not be used directly in shower zones.

Revised 13.05.2025

Symbols







Technical data

Type:	Water-based acrylic dispersion paint
Color:	White, A, B, and C base
Gloss:	Matte 05
Density:	1.3
Solids (by volume %):	Approx. 40%
Application method:	Brush, roller, or spray. Spraying should be done by professionals. A roller with an extension pole is recommended to help avoid streaks.
Thinner/ cleaning agent:	Water
Recommended coverage:	8–10 m ² /liter, depending on the substrate
Nozzle size:	
Recommended film thickness, dry:	0.43–0.53 mm (0.017–0.021")
Fan angle:	50°–80°
Spray pressure:	Min. 15 MPa (Min. 150 kg/cm ²)
Drying time (at 23°C, 50% R.H.):	1 hour
Recoating interval, minimum:	4 hours
Minimum application temperature:	+10°C. Best results are achieved when applied at room temperature.

Pretreatment

The surface must be clean and dry. Clean with Gjøco Interiørvask or Gjøco Gulv- og Panelrens. Follow the instructions on the packaging. Previously oil-painted surfaces, MDF boards, and hard, smooth substrates should be sanded to a matte finish and primed with Gjøco Sperregrunn. A test application

	is recommended if there is any uncertainty about whether the surface is suitable for painting.
Directions for use	Apply evenly and generously. On absorbent and porous surfaces, 3 coats are recommended to avoid streaks. Using a roller with an extension pole is advisable, as it helps reduce the risk of streaking. For an even finish, it is recommended to roll full lengths in the same direction across the entire wall.
Color	Use the same batch number for the same coat and surface to avoid differences in gloss and color. Alternatively, different batch numbers can be mixed together before use. Buckets where the color has been mixed using different mixing machines and/or at different times may result in shade variations. Be aware of this if additional paint is needed for the same project later on.
Storage	Close the lid tightly when storing the paint to prevent spills and drying out. The paint must be transported and stored upright, in a dry, frost-free environment.
Ecolabelling	<p>Gjøco Våtrom 05 is approved by the Norwegian Ecolabelling organization and meets the requirements for the Nordic Swan Ecolabel.</p>  <p>The product has been tested according to the testing requirements set by BREEAM-NOR. The product complies with BREEAM-NOR HEA 02. Gjøco Våtrom 05 contains no substances listed on the A20 list.</p>
Disposal of waste	<p>Liquid paint must not be poured into drains or released into nature, but should be delivered to an approved hazardous waste disposal facility.</p>   
Other information	<p>The application temperature for both air and substrate must be at least +10°C. Painted surfaces must cure for a minimum of 4 weeks before cleaning with a mild detergent. Light marks on dark surfaces can be removed with a microfiber cloth and clean water. Stir well before use.</p> <p>Packaging sizes: 0.68 L and 2.7 L.</p>
Safety	<p>See the separate safety data sheet. Read the information on the packaging.</p> <p>The EU limit value for this product (category A/a): 30 g/l (2010). This product contains: <1 g/l VOC.</p>

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished products and as the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the product's quality. The products are delivered in accordance with our general terms and conditions for sales, delivery and service, unless otherwise agreed in writing. We reserve the right to make minor product changes and to change the specified data without prior notice. This data sheet replaces previous editions.

Contact information**Gjøco AS**

Ørvegen 1160, 6639 Torvikbukt, Norway

Telephone: +47 712 91 700

E-mail: office@gjoco.no

