

Product Data Sheet

Gjøco Proff Rullesparkel Allround



Gjøco Proff Rullesparkel Allround is a ready-mixed, gray all-purpose filler. It has excellent filling properties and a smooth consistency, making it easy to work with. Suitable for re-surfacing, joint filling, and full-surface filling. Ideal for most indoor substrates on wall and ceiling surfaces, such as concrete, gypsum, fabric wallpaper, and existing wallpaper. It is also suitable for embedding paper strips.

Revised 05.12.2024

Symbols



Technical Data

Type:	Latex polymer
Color:	Gray
Filler:	Light filler and white dolomite
pH:	Approx. 9
Grain Size:	Max 0,2 mm
Application Method:	Roller, can also be sprayed
Thinner/Cleaning Agent:	Water (typically not thinned)
Coverage:	Joint filling on gypsum boards: Approx. 0.3 liters/m ² . Full-surface filling with 1 mm thickness: Approx. 1 liter/m ² .
Drying Time:	Depends on substrate, layer thickness, temperature, and humidity
Minimum Application Temperature:	+5 °C
Shelf Life:	1 year in unopened packaging

Surface Preparation

The substrate must be clean, dry, free from grease, and without loose particles. Glossy and contaminated surfaces should be cleaned with Gjøco Interiørvask.

Application

Apply with a roller. The substrate temperature must be at least +5°C. Once the surface is dry, sand it with sandpaper of grain size 150–180. Eye and respiratory protection are recommended during sanding. Dust off the surface before the next treatment. Surfaces that have been filled should be primed before wallpapering.

Environmental Labeling

Gjøco Proff Rullesparkel Allround is approved by Miljømerking Norge and meets the criteria for the Swan environmental label.



The product has been tested according to the requirements set by BREEAM-NOR (2016), meeting BREEAM-NOR HEA 02. Gjøco Proff Rullesparkel Allround does not contain substances listed on the A20 list.

Storage

The product is a date-marked perishable good. Unopened packaging can be stored in a dark and frost-free environment for a maximum of 12 months. Once opened, the container should be tightly sealed. The product should be transported and stored upright, in a dry and frost-free location.

Waste Disposal

The filler and cleaning water should not be disposed of in sewage or nature. They should be taken to a certified hazardous waste facility. Empty, clean, and dry plastic packaging without handles can be disposed of as plastic waste.

**Additional Information**

Store in a dry, frost-free location, away from direct sunlight. Unopened packaging can be stored for 12 months. It may remain usable after 12 months; check consistency and smell. Packaging size: 12 L.

Safety

Refer to the safety data sheet. Follow the information on the packaging. Eye and respiratory protection are recommended when sanding larger surfaces.

The information on this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and since conditions of use are often beyond our control, we can only guarantee the product's quality. Products are supplied according to our general terms of sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and update the stated data without prior notice. This data sheet supersedes earlier versions.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Phone: +47 712 91 700
Email: office@gjoco.no

